

301-CI8601-0500

Multi-Conductor – Unshielded Twisted Pair Cable



DESCRIPTION

14 AWG stranded (42x30) tinned copper conductors, PVC insulation, twisted pair, PVC jacket.

APPLICATION

Multipair Audio, Control and Instrumentation Cable for Industrial, Data, Interconnect and Analogue Audio used.

PHYSICAL CHARACTERISTICS

Conductor

AWG

Pair	AWG	Stranding	Conductor Material
1	14	42x30	TC – Tinned Copper

Insulation

Insulation Material

Insulation Material	Wall Thickness (mm)
PE – Polyethylene	0.81

Outer Shield

Outer Shield Material

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC – PolivinyI Chloride	0.869

Overall Cabling

Overall Nominal Diameter : 8.6 mm

Pair

Pair Color Code Chart

Number	Color
1	Black & Clear

Mechanical Characteristics (Overall Cable)

Operating Temperature Range	-20°C to 80°C
Temperature Rating	80°C
Max Pulling Tension	55 Kg
Min. Bend Radius	88.600 mm

Applicable Specifications and Agency Compliance (Overall Cable)

Applicable Standards

EU CE Mark (Y/N)	Yes
EU Directive 2002/95/EC (RoHS) (Y/N)	Yes
EU RoHS (Y/N)	Yes

Electrical Characteristics (Overall Cable)

Nom. Inductance

Inductance (µH/m)

0.62339

Nom. Capacitance Conductor to Conductor

Capacitance (pF/m)

72.180

Nom. Conductor DC Resistance

DCR@20°C (Ohm/km)

9.3

Max. Operating Voltage

Voltage

300-600

Max. Operating Current

Current/Cond. @ 20°C

9.6 Amps

Part Number

301-CI8601-0500	1 Pair 14 AWG Unshielded Twisted Cable
-----------------	--

Product Family

301-CI8701-0500	1 Pair 12 AWG Unshielded Twisted Cable
-----------------	--

301-CI8601-0500	1 Pair 14 AWG Unshielded Twisted Cable
-----------------	--

301-CI8501-0500	1 Pair 16 AWG Unshielded Twisted Cable
-----------------	--

301-CI8401-0500	1 Pair 18 AWG Unshielded Twisted Cable
-----------------	--

301-CI8 xx-0yzz

Substitute : xx = Number of Pair

y : 3= 305m/Box, 5=500m/reel, 1=1000m/reel

zz : 00 = PVC, LS = LSZH(Orange colour jacket)

Other sizes from 30AWG to 10AWG are available upon request

NGUYEN TRUNG DUC

Phone: 0985 72 72 32

Skype: trungduc.0290

duc.nguyen@ulcab.com.vn

WEB : ulcab.com.vn

© Alantek Communications USA

All Right Reserved.

Alantek® Communications USA 2006. This information provides a general description of product and shall not form part of any contract. Improvement or changes may be made to the product without advanced notification.