


TX5e™ Category 5e UTP Copper Cable

PANDUIT®

SPECIFICATION SHEET

specifications

Category 5e cable shall meet ANSI/TIA-568-C.2 and IEC 61156-5 Category 5e component standards. The conductors shall be 24 AWG copper insulated with HDPE polymer. The copper conductors shall be twisted in pairs and all four pairs shall be covered by a low smoke zero halogen or flame retardant PVC jacket.



technical information

Electrical performance:	Certified performance in a 4-connector configuration up to 100 meters, meets ANSI/TIA-568-C.2, ISO 11801 2nd Edition Class D and IEC 61156-5 Category 5e channel and component requirements
Conductor/insulator:	24 AWG solid copper insulated with HPDE
Flame rating:	LSZH – IEC 60332-1, 60754-2, 61034 PVC (CM) – UL 1685 PVC (CMR) – UL 1666
PoE compliance:	Meets IEEE 802.3af and IEEE 802.3at for PoE applications
Installation tension:	110N (25 lbf) maximum
Temperature rating:	0° to 50°C (32° to 122°F) during installation -20° to 75°C (14° to 167°F) during operation
Cable jacket:	LSZH – Low Smoke Zero Halogen PVC (CM) – PVC PVC (CMR) – Flame retardant PVC
Cable diameter:	LSZH – 5.0mm (0.197 in.) nominal PVC (CM), PVC (CMR) – 4.8mm (0.189 in.) nominal
Cable weight:	LSZH – 9 kg/305m (20 lbs./1000 ft.) PVC (CM) – 8 kg/305m (18 lbs./1000 ft.) PVC (CMR) – 8.5 kg/305m (19 lbs./1000 ft.)
Packaging:	305m (1000 ft.) easy-pay-out box LSZH – 11 kg/305m (23 lbs./1000 ft.) PVC (CM) – 10 kg/305m (21 lbs./1000 ft.) PVC (CMR) – 10.5 kg/305m (22 lbs./1000 ft.) Packaged tested to ISTA procedure 1A

key features and benefits

Third party tested	Cable has been tested as part of the TX5e™ Category 5e UTP Copper Cabling System by an independent laboratory and complies with the electrical channel requirements of the following standard: ANSI/TIA-568-C.2 Category 5e standard
Descending length cable markings	Easy identification of remaining cable reduces installation time and cable scrap
Tested beyond the standards	Cable has been characterized to 350 MHz, 250 MHz above the standard
Easy payout box	Ensures proper performance and provides quick installation

applications

TX5e™ UTP Copper Cable is a component of the Panduit® TX5e™ UTP Copper Cabling System. This end-to-end system provides Gigabit Ethernet performance with usable bandwidth beyond 100 MHz. With certified performance to the ANSI/TIA-568-C.2 Category 5e and ISO 11801 Class D standards, this system will support the following applications:

- Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 1000BASE-T (Gigabit Ethernet)
- 115 Mb/s ATM, 622 Mb/s ATM
- Token ring 4/16

www.panduit.com

TX5e™ UTP Copper Cabling System

TX5e™ UTP Copper Cable

LSZH:	PUL5C04BU-C*
CM:	PUC5C04BU-C*
CMR:	PUR5C04BU-C*

Mini-Com® TX5e™ PLUS UTP Jack Module

Jack module:	CJ5E88TGIWY**
---------------------	---------------

TX5e™ UTP Patch Cords – CM

Foot lengths:	UTPCH3^Y
Meter lengths:	UTPCH1^MY

TX6™ PLUS UTP Patch Cords – LSZH

Foot lengths:	UTPCHL3^Y
Meter lengths:	UTPCHL^MY

DP5e™ Punchdown Patch Panels

Angled, 24-port, 1RU:	DPA245E88TGY
Angled, 48-port, 2RU:	DPA485E88TGY
Flat, 24-port, 1RU:	DP245E88TGY
Flat, 48-port, 2RU:	DP485E88TGY

Mini-Com® Flush Mount Modular Patch Panels

Angled, 24-port, 1RU:	CPPA24FMWBLY
Angled, 48-port, 2RU:	CPPA48FMWBLY
Flat, 24-port, 1RU:	CPP24FMWBLY
Flat, 48-port, 2RU:	CPP48FMWBLY

Termination and Cable Prep Tools

Termination tools:	EGJT or TGJT
Conductor stripping tool:	CWST
Conductor stripping tool:	CJAST

*For standard cable colors other than BU (Blue), replace BU in part number with WH (White) or IG (International Gray). Standard pallets are configured in 4 layers, 9 cartons per layer, total of 36 cartons per pallet. Add E to end of part number for European pallets which are configured in 4 layers, 6 cartons per layer, total of 36 cartons per pallet.

**For standard colors other than Off White (IW), replace suffix with EI (Electrical Ivory), IG (International Gray), AW (Arctic white), WH (White), BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), or VL (Violet). Add -24 to end of part number for 24 pack convenience package.

^For standard foot lengths other than 3 feet, replace the 3 in the part number with 1 to 20 (one foot increments) 25, 30, 35 or 40. For standard colors other than Off White, add suffix BU (Blue), RD (Red), YL (Yellow), or GR (Green) before the Y at the end of the part number. For example, the part number for a blue, CM, Category 5e, 5-foot patch cord is UTPCH5BUY.


^^For standard meter lengths other than 1 meter, replace the 1 in the part number with 1-10 meters (one meter increments) 0.5, 1.5, 2.5, 15, or 20. For standard colors other than Off White, add suffix BU (Blue), RD (Red), YL (Yellow), or GR (Green) before Y at the end of the part number. For example, the part number for a blue, CM, Category 5e, 5-meter patch cord is UTPCH5MBUY.

TX5e™ Category 5e UTP Copper Cable

Additional Specifications

Mechanical Test	
<i>Ultimate Breaking Strength</i>	>400 N (90 lbf)
<i>Minimum Bend Radius</i>	4 x cable diameter
Electrical Test	
<i>DC Resistance</i>	<9.38 Ohm per 100m (328 ft.)
<i>DC Resistance Unbalance</i>	<5%
<i>Mutual Capacitance</i>	<5.6 nF per 100m (328 ft.)
<i>Capacitance Unbalance</i>	<330 pF per 100m (328 ft.)
<i>Characteristic Impedance</i>	100 Ohm +/-15% up to 100 MHz
<i>Nominal Velocity of Propagation (NVP)</i>	65%

Cable Construction



WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800-777-3300 and reference COSP167

PANDUIT®

©2011 Panduit Corp.
ALL RIGHTS RESERVED.

WW-COSP167

5/2011