



**Info**

- Conductor cross-section up to 120 mm<sup>2</sup>
- Oil-resistant according to EN 50363-4-1: TM5
- Missing dimensions: See ÖLFLEX® 150 CY

**ÖLFLEX® 191 CY**

**Screened and oil-resistant multi-standard cable with AWM approval**

LAPP KABEL STUFGART ÖLFLEX 191 CY

**Benefits**

- High electrical performance due to 4 kV test voltage
- Multifunctional application possibilities

**Application range**

- Plant engineering  
Industrial machinery  
Heating and air-conditioning systems
- In EMC-sensitive environments (electromagnetic compatibility)
- Mainly used in dry, damp and wet interiors (including water-oil mixtures), but not for outdoor use
- For fixed installation under medium mechanical load conditions, and applications with occasional flexing at free, non-continuously recurring movement without tensile load or compulsory guidance
- Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79 Ed. 2012: please see the catalogue appendix table T29

**Product features**

- Flame-retardant according to IEC 60332-1-2 and UL 1581 §1061 Cable Flame Test
- Oil-resistant according to EN 50363-4-1: TM5
- High degree of screening  
low transfer impedance  
(max. 250 Ω/km at 30 MHz)

**Norm references / Approvals**

- UL AWM Style 21098 or 2587  
CSA AWM I A/B II A/B
- Multi-standard cables have conductor strands with nominal sizes in mm<sup>2</sup> or AWG/kcmil. The master size is mentioned in the table below, while the equivalent size of the other system can be found in the Appendix T16 of this catalogue. For this related secondary size the cross-section of the conductor mostly works out to be greater than the specified nominal value.

**Product make-up**

- Fine-wire strand made of bare copper wires
- PVC core insulation
- PVC inner sheath, grey
- Tinned-copper braiding
- PVC outer sheath, high oil-resistance, grey (RAL 7001)

**Technical data**

- Classification**  
ETIM 5.0 Class-ID: EC000104  
ETIM 5.0 Class-Description: Control cable
- Core identification code**  
Black with white numbers acc. to VDE 0293-1
- Specific insulation resistance**  
> 20 GOhm x cm
- Conductor stranding**  
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**  
Occasional flexing: 20 x outer diameter  
Fixed installation: 6 x outer diameter
- Nominal voltage**  
HAR U<sub>0</sub>/U: 300/500 V  
UL/CSA: 600 V
- Test voltage**  
4000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
Occasional flexing:  
HAR: -5°C to +70°C  
UL/CSA: -5°C to +90°C  
Fixed installation:  
HAR: -40°C to +70°C  
UL/CSA: -40°C to +90°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0011234	7 G 0.75	10.5	85.9	187
0011202	2 X 1.0	8.4	48.0	126
0011180	3 G 1.0	8.8	55.8	122
0011181	4 G 1.0	9.6	80.8	157
0011182	5 G 1.0	10.3	89.4	183
0011183	7 G 1.0	11.2	99.9	207
0011184	12 G 1.0	14.6	175.7	342
0011185	18 G 1.0	17.0	241.7	472
0011186	25 G 1.0	20.1	341.7	648
0011302	2 X 1.5	9.0	64.7	156
0011187	3 G 1.5	9.6	89.1	166
0011188	4 G 1.5	10.3	96.6	191
0011189	5 G 1.5	11.3	111.2	222
0011190	7 G 1.5	12.1	145.2	270
0011191	12 G 1.5	16.1	257.0	464
0011192	18 G 1.5	18.7	382.8	679
0011193	25 G 1.5	23.0	546.2	952
0011194	3 G 2.5	10.8	111.1	221
0011195	4 G 2.5	11.4	140.6	269

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0011196	5 G 2.5	12.9	167.3	325
0011197	7 G 2.5	14.1	240.0	421
30010542	12 G 2.5	17.9	414.9	769
30010543	18 G 2.5	22.0	626.1	1102
30010544	4 G 4	13.6	236.7	462
30010545	5 G 4	14.9	277.8	535
30010546	7 G 4	16.2	393.4	735
30010548	4 G 6	15.8	317.1	574
3023130	5 G 6	17.3	413.7	737
30010547	7 G 6	18.8	563.8	950
3023131	4 G 10	19.5	550.4	946
30010639	4 G 16	24.7	819.1	1189
3023132	4 G 25	28.5	1,165.0	1692
30010928	4 G 35	31.7	1,683.0	2700
3026535	4 G 50	39.7	2,342.0	3362
3025946	4 G 70	44.8	3,229.0	4490
3025947	4 G 95	50.0	4,010.0	5540
3026536	4 G 120	61.3	5,012.0	6960

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 600 m drum or 8 x 75 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- ÖLFLEX® 150 CY refer to page 47
- ÖLFLEX® CONTROL TM CY refer to page 51
- ÖLFLEX® TRAY II CY refer to page 53

**Accessories**

- SKINTOP® MS-SC-M refer to page 674
- SKINTOP® MS-M BRUSH refer to page 675
- KT cable shears refer to page 908