



ÖLFLEX® 450 P

Abrasion-resistant cable for handheld equipment with integrated wear indicator



Info

- Cost-effective PVC/PUR dual sheath
- Integrated wear indicator

Benefits

- Good cost-benefit ratio
- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- The signal colour of the outer sheath increases safety and visual perception
- Serious mechanical damages of the yellow outer jacket become visible due to the red inner sheath

Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Power or extension cord
- Portable devices for the home and garden
- Outdoor use is possible within the indicated operating temperature range

Product features

- Good oil resistance
- Abrasion and notch-resistant
- Flame-retardant according IEC 60332-1-2
- Low-adhesive surface
- Resistant to hydrolysis and microbes

Norm references / Approvals

- Based on VDE 0250 / 0285

Product make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Based on PVC
- Cores twisted together
- Inner sheath: PVC - colour red
- Outer sheath: PUR - colour yellow

Technical data

- Classification**
 ETIM 5.0 Class-ID: EC001578
 ETIM 5.0 Class-Description: Flexible cable
- Core identification code**
 Colours according to VDE 0293-308, refer to Appendix T9
- Specific insulation resistance**
 > 20 GOhm x cm
- Conductor stranding**
 Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**
 Occasional flexing: 15 x outer diameter
 Fixed installation: 4 x outer diameter
- Nominal voltage**
 U_0/U : 300/500 V
- Test voltage**
 3000 V
- Protective conductor**
 G = with GN-YE protective conductor
 X = without protective conductor
- Temperature range**
 Occasional flexing: -5°C to +70°C
 Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 450 P				
0012101	2 X 1.0	8.0	19.2	82
0012102	3 G 1.0	8.4	29.0	89
0012202	3 G 1.5	9.3	43.0	120
00122033	4 G 1.5	10.1	58.0	160
00122043	5 G 1.5	10.9	72.0	179
0012302	3 G 2.5	10.8	72.0	186
00123043	5 G 2.5	13.6	120.0	283

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® 540 P refer to page 77
- ÖLFLEX® 550 P* refer to page 79

Accessories

- SKINTOP® BS-M refer to page 661
- SKINTOP® ST-M refer to page 654