



ÖLFLEX® 550 P*

PUR power cords with European harmonisation (HAR)

Info

- High mechanical strength
- Good oil resistance
- H05BQ-F/H07BQ-F design standard



Benefits

- Harmonised use in Europe
- Increased durability under harsh conditions thanks to robust PUR outer sheath
- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- Wide temperature range for applications in harsh climatic environments
- The signal colour of the outer sheath increases safety and visual perception

Application range

- Portable handheld electrical devices such as drills, sanders, jig saws or grinders
- Building sites, camp sites, stage applications
- Construction machinery
- Agricultural equipment
- For indoor and outdoor use

Product features

- Oil-resistant
- Abrasion and notch-resistant
- Flexible down to -40°C
- Resistant to hydrolysis and microbes

Norm references / Approvals

- EN 50525-2-21
- H05BQ-F/H07BQ-F design standard

Product make-up

- Fine-wire strand made of bare copper wires
- Core insulation: rubber compound
- Cores twisted together
- PUR outer sheath
- Sheath colour: orange

Technical data

- Core identification code**
Colours according to VDE 0293-308, refer to Appendix T9
- Specific insulation resistance**
> 10 GOhm x cm
- Conductor stranding**
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**
For flexible use:
12.5 x outer diameter
Fixed installation: 4 x outer diameter
- Nominal voltage**
Up to 1.0 mm²: U₀/U: 300/500 V
From 1.5 mm²: U₀/U: 450/750 V
- Test voltage**
3000 V
- Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- Temperature range**
Occasional flexing: -40°C to +90°C
Fixed installation: -50°C to +90°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® 550 P U₀/U: 300/500 V				
0013600	2 X 0.75	5.7 - 7.4	14.4	50
0013601	3 G 0.75	6.2 - 8.1	21.6	64
00136023	4 G 0.75	6.8 - 8.8	28.8	78
00136033	5 G 0.75	7.6 - 9.9	36.0	98
0013610	2 X 1.0	6.1 - 8.0	19.2	60
0013611	3 G 1.0	6.5 - 8.5	29.0	74
00136123	4 G 1.0	7.1 - 9.3	38.4	92
00136133	5 G 1.0	8.0 - 10.3	48.0	114
ÖLFLEX® 550 P U₀/U: 450/750 V				
0013620	2 X 1.5	7.6 - 9.8	29.0	87
0013621	3 G 1.5	8.0 - 10.4	43.0	108
00136223	4 G 1.5	9.0 - 11.6	58.0	137
00136233	5 G 1.5	9.8 - 12.7	72.0	165
0013630	2 X 2.5	9.0 - 11.6	48.0	90
0013631	3 G 2.5	9.6 - 12.4	72.0	161
00136323	4 G 2.5	10.7 - 13.8	96.0	206
00136333	5 G 2.5	11.9 - 16.3	120.0	254

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
* Trade product, no Lapp product
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® ROBUST 200 refer to page 66
- H05RN-F refer to page 81
- H07RN-F refer to page 82
- ÖLFLEX® 500 P refer to page 76
- ÖLFLEX® 540 P refer to page 77

Accessories

- Cutting tools for various applications refer to page 907
- Stripping tools refer to page 909
- SKINTOP® MS-M refer to page 666
- SKINTOP® ST-M refer to page 654
- SKINTOP® BS-M METAL / SKINTOP® BSR-M METAL refer to page 668