



New

ÖLFLEX® CLASSIC 100 H

Halogen-free power and control cable, oil resistant and very flexible

LAPP KABEL STÜTTGART ÖLFLEX® CLASSIC 100 H HFFR CE

Info

- New improved version!

Benefits

- Easy handling and installation due to very flexible cable type

Application range

- Public buildings
- Airport, railway station
- Plant engineering
Industrial machinery
Heating and air-conditioning systems
- Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards

Product features

- Flame-retardant according to IEC 60332-1-2 (flame spread on a single cable)
- No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)
- Halogen-free according to IEC 60754-1 (amount of halogen acid gas)
Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)
- Low smoke density according to IEC 61034-2
- Oil-resistant according to EN 50363-4-1 (TM5) and UL OIL RES I and UL OIL RES II
- Ozone-resistant according to EN 50396

Norm references / Approvals

- Based on IEC 60227-5 and EN 50525-2-51
- Based on EN 50525-2-11

Product make-up

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free
- Outer sheath made of special halogen-free compound, grey (RAL 7001)

Technical data

- Core identification code**
Colours according to VDE 0293-308, refer to Appendix T9
- Specific insulation resistance**
> 20 GOhm x cm
- Conductor stranding**
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**
Occasional flexing: 15 x outer diameter
Fixed installation: 4 x outer diameter
- Nominal voltage**
U0/U: 450/750 VAC
In protected and fixed installations:
U0/U: 600/1000 V
- Test voltage**
4000 V
- Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- Temperature range**
Occasional flexing: -30°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0014150	2 X 1.5	7.6	28.8	91
0014151	3 G 1.5	8.3	43.2	114
0014152	4 G 1.5	9.0	57.6	140
0014153	5 G 1.5	10.1	72.0	176
0014156	2 X 2.5	9.0	48.0	133
0014157	3 G 2.5	9.7	72.0	167
0014158	4 G 2.5	10.8	96.0	207
0014159	5 G 2.5	11.9	120.0	260
0014162	3 G 4	11.4	115.2	240
0014163	4 G 4	12.7	153.6	303
0014164	5 G 4	13.9	192.0	372
0014166	3 G 6	12.7	172.8	320
0014167	4 G 6	13.9	230.4	400
0014168	5 G 6	15.8	288.0	510
0014170	4 G 10	17.9	384.0	662
0014171	5 G 10	19.9	480.0	826
0014173	4 G 16	20.7	614.4	957
0014174	5 G 16	23.0	768.0	1193
0014176	4 G 25	25.4	960.0	1480
0014177	5 G 25	28.5	1,200.0	1860
0014179	4 G 35	28.8	1,344.0	1985
0014180	5 G 35	32.3	1,680.0	2490
0014182	4 G 50	35.0	1,920.0	2830
0014184	4 G 70	40.0	2,688.0	3890
0014186	4 G 95	46.0	3,648.0	5110
0014188	4 G 120	51.0	4,608.0	6315

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Single lengths for sizes: ≥ 4G50 max. 500 m; ≥ 4G120 max. 400 m
 Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 130 H BK 0,6/1kV refer to page 63

Accessories

- SKINTOP® ST-HF-M refer to page 660

ÖLFLEX®
UNITRONIC®
ETHERLINE®
HITRONIC®
EPIC®
SKINTOP®
SILVYN®
FLEXIMARK®
ACCESSORIES
APPENDIX