



## ÖLFLEX® CLASSIC 130 H BK 0,6/1kV

VDE-tested characteristics

**Info**

- Outdoors
- Public buildings



**Benefits**

- Easy installation due to flexible design

**Application range**

- Public buildings
- Plant engineering
- Industrial machinery
- Heating and air-conditioning systems
- Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards
- For outdoor applications
- Note: for the use of AWM (Appliance Wiring Material) cables in industrial machinery (USA) according to NFPA 79 Ed. 2012: please see the catalogue appendix table T29

**Product features**

- Flame-retardant according to IEC 60332-1-2 (flame spread on a single cable)
- No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)
- Halogen-free according to IEC 60754-1 (amount of halogen acid gas)
- Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)
- Low smoke density according to IEC 61034-2
- UV and weather-resistant according to ISO 4892-2
- Ozone-resistant according to EN 50396

**Norm references / Approvals**

- Based on EN 50525-3-11
- UL AWM single core style 10559 is introduced into the serial manufacturing and step by step into the stock
- UL AWM jacket style 21288 is introduced into the serial manufacturing and step by step into the stock

**Product make-up**

- Fine-wire strand made of bare copper wires
- Core insulation: Halogen-free
- Outer sheath made of special halogen-free compound, black (RAL 9005)

**Technical data**

- Core identification code**  
Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9  
From 6 cores: black with white numbers
- Specific insulation resistance**  
> 20 GOhm x cm
- Conductor stranding**  
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter
- Nominal voltage**  
U<sub>c</sub>/U: 600/1000 V  
UL: 1000 V
- Test voltage**  
4000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
Occasional flexing: -15°C to +70°C  
Fixed installation: -40°C to +80°C  
UL: +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - coloured cores</b>				
1123410	2 X 1.0	8.6	19.2	107
1123411	3 G 1.0	9.0	28.8	123
1123412	4 G 1.0	9.6	38.4	144
1123413	5 G 1.0	10.4	48.0	167
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - numbered cores</b>				
1123414	7 G 1.0	11.1	67.2	206
1123415	12 G 1.0	14.0	115.2	314
1123416	18 G 1.0	16.1	172.8	428
1123417	25 G 1.0	18.6	240.0	569
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - coloured cores</b>				
1123418	2 X 1.5	9.6	28.8	137
1123419	3 G 1.5	10.1	43.2	161
1123420	4 G 1.5	10.8	57.6	190
1123421	5 G 1.5	11.7	72.0	221
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - numbered cores</b>				
1123422	7 G 1.5	12.6	100.8	276
1123423	12 G 1.5	16.1	172.8	427
1123424	18 G 1.5	18.8	259.2	596
1123425	25 G 1.5	21.7	360.0	799
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - coloured cores</b>				
1123426	2 X 2.5	10.8	48.0	184

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
1123427	3 G 2.5	11.3	72.0	219
1123428	4 G 2.5	12.2	96.0	262
1123429	5 G 2.5	13.3	120.0	307
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - numbered cores</b>				
1123430	7 G 2.5	14.4	168.0	390
1123431	12 G 2.5	18.7	288.0	624
1123432	18 G 2.5	22.0	432.0	879
1123433	25 G 2.5	25.8	600.0	1212
<b>ÖLFLEX® CLASSIC 130 H 0,6/1 kV - coloured cores</b>				
1123434	3 G 4	12.6	115.2	290
1123435	4 G 4	13.7	153.6	351
1123436	5 G 4	14.9	192.0	416
1123437	3 G 6	13.9	172.8	377
1123438	4 G 6	15.1	230.4	463
1123439	5 G 6	16.8	288.0	559
1123440	4 G 10	18.7	384.0	757
1123441	5 G 10	20.7	480.0	915
1123442	4 G 16	21.3	614.4	1070
1123443	5 G 16	23.6	768.0	1296
1123444	4 G 25	26.2	960.0	1631

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- ÖLFLEX® CLASSIC 110 H refer to page 56
- ÖLFLEX® CLASSIC 130 H refer to page 60

**Accessories**

- SKINTOP® ST-HF-M refer to page 660