

Harsh conditions

High mechanical and chemical resistance



ÖLFLEX® CLASSIC 400 CP

Screened and abrasion-resistant control cables with PUR sheath for increased application requirements



Info

- High mechanical strength
- Good oil resistance
- EMC compliant copper screening

Technical data

Classification
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable

Core identification code
Black with white numbers acc. to VDE 0293-1

Specific insulation resistance
> 20 GOhm x cm

Conductor stranding
Fine wire according to VDE 0295, class 5/IEC 60228 class 5

Minimum bending radius
Occasional flexing: 20 x outer diameter
Fixed installation: 6 x outer diameter

Nominal voltage
U₀/U: 300/500 V

Test voltage
4000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Benefits

- Increased durability under harsh conditions thanks to robust PUR outer sheath
- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- Copper braiding screens the cable against electromagnetic interference

Application range

- Machine tools
- Industrial machinery and machine tools
- Measurement, control and electrical applications
- Very suitable for oily wet areas within machinery and production lines that are subject to normal mechanical stress
- Outdoor use is possible within the indicated operating temperature range

Product features

- High oil-resistance
- Abrasion and notch-resistant
- EMC-compliant
- Low-adhesive surface
- Resistant to hydrolysis and microbes

Norm references / Approvals

- Based on VDE 0285

Product make-up

- Fine-wire strand made of bare copper wires
- Core insulation: special PVC
- Cores twisted in layers
- PVC inner sheath, grey
- Tinned-copper braiding
- Special polyurethane outer sheath (PUR)
- Sheath colour: silver grey (RAL 7001)

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CLASSIC 400 CP				
1313852	2 X 0.75	7.4	45.0	85
1313103	3 G 0.75	7.9	52.0	99
1313853	3 X 0.75	7.9	52.0	99
1313104	4 G 0.75	8.4	77.0	114
1313854	4 X 0.75	8.4	77.0	114
1313105	5 G 0.75	8.9	84.0	130
1313855	5 X 0.75	8.9	84.0	130
1313107	7 G 0.75	9.7	92.0	161
1313857	7 X 0.75	9.7	92.0	161
1313112	12 G 0.75	12.3	138.0	245
1313118	18 G 0.75	14.5	219.0	354
1313125	25 G 0.75	16.6	277.0	463
1313134	34 G 0.75	18.9	420.0	598
1313141	41 G 0.75	20.6	500.0	725
1313902	2 X 1.0	7.9	50.0	97
1313203	3 G 1.0	8.2	77.0	111
1313903	3 X 1.0	8.2	77.0	111
1313204	4 G 1.0	8.7	87.0	129
1313904	4 X 1.0	8.7	87.0	129
1313205	5 G 1.0	9.5	90.0	152
1313207	7 G 1.0	10.2	110.0	184
1313212	12 G 1.0	13.3	194.0	306
1313218	18 G 1.0	15.5	267.0	417
1313225	25 G 1.0	17.5	379.0	541
1313234	34 G 1.0	20.3	516.0	735

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
1313241	41 G 1.0	22.0	610.0	860
1313952	2 X 1.5	8.5	77.0	116
1313303	3 G 1.5	8.9	85.0	135
1313953	3 X 1.5	8.9	85.0	135
1313304	4 G 1.5	9.6	100.0	162
1313954	4 X 1.5	9.6	100.0	162
1313305	5 G 1.5	10.3	120.0	187
1313955	5 X 1.5	10.3	120.0	187
1313307	7 G 1.5	11.3	152.0	236
1313957	7 X 1.5	11.3	152.0	236
1313312	12 G 1.5	14.8	267.0	392
1313318	18 G 1.5	17.2	400.0	536
1313325	25 G 1.5	20.1	572.0	742
1313334	34 G 1.5	21.9	754.0	960
1313341	41 G 1.5	24.7	874.0	1118
1313403	3 G 2.5	10.3	121.0	191
1313404	4 G 2.5	11.3	163.0	232
1313405	5 G 2.5	12.6	199.0	282
1313407	7 G 2.5	13.9	261.0	370
1313412	12 G 2.5	17.2	470.0	580
1313504	4 G 4	13.4	238.0	345
1313505	5 G 4	14.7	279.0	412
1313604	4 G 6	15.8	318.0	483
1313605	5 G 6	17.3	370.0	576
1313614	4 G 10	19.0	558.0	733
1313624	4 G 16	22.2	804.0	1340

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
DESINA® is a registered trademark of the German Machine Tool Builders' Association
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC 415 CP refer to page 71
- ÖLFLEX® 440 CP refer to page 73
- ÖLFLEX® CLASSIC 415 CP
- ÖLFLEX® 440 CP

Accessories

- Conductor end sleeves refer to page 913
- SKINTOP® MS-SC-M refer to page 674