



## ÖLFLEX® ROBUST 210

Proven all-weather control cables – resistant to a wide range of chemical media

**Info**

- Excellent weather resistance
- Good chemical resistance
- Reduced outer diameter



### Benefits

- Outstanding weather, ozone and UV resistance together with the wide temperature range enable versatile use for both indoor and outdoor applications
- Resistant to contact with plant, animal or synthetic-based organic oils, greases, waxes and the related emulsions
- Good resistance to ammonia compounds and bio-gases
- Good resistance to cold and hot water as well as water-soluble cleaning agents
- Well-suited to frequent steam cleaning

### Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Agricultural equipment
- For indoor and outdoor use

### Product features

- Halogen-free materials
- Good chemical resistance to ester-based hydraulic fluids
- Ozone, UV and weather-resistant according to EN 50396 and HD 605 S2
- Flexible down to -40°C
- Number-coded cores

### Norm references / Approvals

- Based on VDE 0250 / 0285

### Product make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of modified PP
- Cores twisted in layers
- Outer sheath made of special TPE
- Sheath colour: black

### Technical data

- Classification**  
ETIM 5.0 Class-ID: EC000104  
ETIM 5.0 Class-Description: Control cable
- Core identification code**  
Black with white numbers acc. to VDE 0293-1
- Specific insulation resistance**  
> 20 GOhm x cm
- Conductor stranding**  
Fine wire according to VDE 0295, class 5/IEC 60228 class 5
- Minimum bending radius**  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter
- Nominal voltage**  
U<sub>0</sub>/U: 300/500 V
- Test voltage**  
4000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
Occasional flexing: -40°C to +80°C  
Fixed installation: -50°C to +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® ROBUST 210</b>				
0021880	2 X 0.5	4.9	10.0	27
0021881	3 G 0.5	5.2	15.0	33
0021882	3 X 0.5	5.2	15.0	33
0021883	4 G 0.5	5.8	19.2	41
0021884	4 X 0.5	5.8	19.2	41
0021885	5 G 0.5	6.3	24.0	49
0021886	5 X 0.5	6.3	24.0	49
0021888	7 G 0.5	6.9	33.6	64
0021889	7 X 0.5	6.9	33.6	64
0021890	10 G 0.5	8.8	48.0	92
0021891	12 G 0.5	9.1	58.0	106
0021892	18 G 0.5	10.8	86.4	151
0021893	25 G 0.5	12.7	120.0	210
0021897	2 X 0.75	5.5	14.4	35
0021898	3 G 0.75	5.8	21.6	43
0021899	3 X 0.75	5.8	21.6	43
0021900	4 G 0.75	6.3	28.8	49
0021901	4 X 0.75	6.3	28.8	49
0021902	5 G 0.75	6.9	36.0	66
0021903	5 X 0.75	6.9	36.0	66
0021904	7 G 0.75	7.5	50.0	85
0021905	7 X 0.75	7.5	50.0	85
0021907	12 G 0.75	10.1	86.0	144
0021908	18 G 0.75	12.0	130.0	208
0021909	25 G 0.75	14.1	180.0	288
0021910	34 G 0.75	16.3	245.0	386
0021911	41 G 0.75	17.8	296.0	464
0021912	50 G 0.75	19.6	360.0	560
0021913	2 X 1.0	5.8	19.2	42
0021914	3 G 1.0	6.1	28.8	49
0021915	3 X 1.0	6.1	28.8	49
0021916	4 G 1.0	6.6	38.4	63
0021917	4 X 1.0	6.6	38.4	63
0021918	5 G 1.0	7.3	48.0	78
0021919	5 X 1.0	7.3	48.0	78
0021920	7 G 1.0	8.1	67.0	107
0021921	10 G 1.0	10.4	96.0	154

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0021922	12 G 1.0	10.7	115.0	178
0021923	18 G 1.0	12.9	173.0	262
0021924	25 G 1.0	15.0	240.0	357
0021925	34 G 1.0	17.5	326.0	484
0021926	41 G 1.0	19.2	394.0	582
0021927	50 G 1.0	21.0	480.0	703
0021928	2 X 1.5	6.4	29.0	56
0021929	3 G 1.5	6.8	43.0	72
0021930	3 X 1.5	6.8	43.0	72
0021931	4 G 1.5	7.4	58.0	91
0021932	4 X 1.5	7.4	58.0	91
0021933	5 G 1.5	8.3	72.0	108
0021934	5 X 1.5	8.3	72.0	108
0021936	7 G 1.5	9.0	101.0	149
0021937	7 X 1.5	9.0	101.0	149
0021938	10 G 1.5	11.8	143.0	215
0021940	12 G 1.5	12.2	173.0	234
0021941	18 G 1.5	14.6	259.0	369
0021942	25 G 1.5	17.2	360.0	510
0021943	34 G 1.5	19.8	490.0	683
0021945	50 G 1.5	24.0	720.0	999
0021946	2 X 2.5	7.6	48.0	86
0021947	3 G 2.5	8.3	72.0	115
0021949	4 G 2.5	9.0	96.0	131
0021951	5 G 2.5	10.1	120.0	178
0021953	7 G 2.5	11.2	168.0	241
0021954	12 G 2.5	15.1	288.0	405
0021963	3 G 4	10.1	115.0	180
0021964	4 G 4	11.1	157.0	228
0021965	5 G 4	12.4	192.0	280
0021966	7 G 4	13.6	269.0	377
0021967	4 G 6	13.3	230.0	332
0021968	5 G 6	14.8	288.0	407
0021969	4 G 10	16.5	384.0	541
0021970	5 G 10	18.4	480.0	620
0021971	4 G 16	18.8	614.0	806
0021972	4 G 25	23.5	960.0	1218
0021973	4 G 35	26.4	1,344.0	1658

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Single lengths for sizes: ≥ 4G16 max. 600 m; ≥ 4G25 max. 300 m; ≥ 4G50 max. 250 m  
Photographs are not to scale and do not represent detailed images of the respective products.