



1U Cat 6 24-port Unshielded Dual IDC Patch Panel c/w Front Cable Management

Features

- Dual IDC allows both 110 and Krone tools to be used for termination
- Comes with front labels
- Comes with front wire management
- Support both T568A and T568B wiring
- Support Gigabit Ethernet application



Electrical Characteristics

IDC	Current Rating	Voltage Rating	Contact Resistance	DC Resistance	Insulation Resistance	Dielectric Withstand Voltage
22-26 AWG Solid Wire	1.5 amp (max)	150 V	20 mΩ	0.1 Ω (max)	500 mΩ	1000 VAC @ RMS, 60 Hz 1 min

Mechanical Characteristics

IDC Termination	IDC Punch Down Cycle	Pull force	Housing	PCB	RJ45 Jack	RJ45 Jack Insertion Cycle
Dual (110 & Krone)	> 250 cycles (min.)	20lb (89N)	PC UL94V-0	FR4 1.6mm (0.4") thickness	8P8C 50u" gold plated	> 2000 cycles (min)

Standards

- ANSI/TIA-568-C.2
- ISO/IEC 11801
- CENELEC EN50173
- UL 1863

Part Number #	Description
302-201601-24AB	24 Port Cat 6 Unshielded Dual IDC Patch Panel c/w Front Wire Management