

PF8VNT3-UK

APC Performance SurgeArrest 8 outlets with Phone, Coax & Network Protection 230V UK



Overview

Model Name	<![CDATA[APC Performance SurgeArrest 8 outlets with Phone, Coax & Network Protection 230V UK]]>
Includes	1.8 Meter Tel cable (2) , 60 cm coaxial cable , 6ft Network cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Bahrain , Botswana , Cyprus , Eritrea , Gambia , Ghana , Gibraltar , Hong Kong , Iraq , Ireland , Jordan , Kenya , Kuwait , Malawi , Malaysia , Malta , Netherlands , Nigeria , Oman , Saudi Arabia , Sierra Leone , Singapore , Sudan , TANZANIA, UNITED REPUBLIC OF , United Arab Emirates , Zambia

Output

Output Power Capacity	0 Watts / 0 VA
Max Configurable Power (Watts)	0 Watts / 0 VA

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	British BS1363A
Cord Length	3.05 meters
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	0 hour(s)
RBC Quantity	0

Communications & Management

Available SmartSlot™ Interface Quantity	0
---	---

Surge Protection and Filtering

Surge energy rating	2525 joules
Data Line Protection	Cable modem / Video protection , RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines) , RJ45 10/100 Base-T Ethernet protection

Physical

Maximum Height	372.0 mm
Maximum Width	122.0 mm
Maximum Depth	42.0 mm
Rack Height	0 U
Net Weight	1.23 kg
Shipping Weight	1.32 kg
Shipping Height	381.0 mm
Shipping Width	216.0 mm
Shipping Depth	51.0 mm
Master Carton Units	12.0
Master Carton Weight	35.0 lbs
Color	Charcoal
SCC Codes	1073130422367 9
Units per Pallet	60.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-15000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	0.000 dB

Conformance

Approvals	CE
Standard warranty	5 years (all other countries) , Lifetime (European Union countries only)
Equipment protection policy	Lifetime : 100000 Euro , Lifetime : 75000 GBP

Sustainable Offer Status

RoHS	Compliant
------	-----------