



Overview

Model Name	APC Home/Office SurgeArrest 6 outlets with Phone Protection 230V UK
Includes	Telephone Cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Bahrain , Botswana , Cyprus , Eritrea , Gambia , Ghana , Gibraltar , Hong Kong , Iraq , Ireland , Jordan , Kenya , Kuwait , Malawi , Malaysia , Malta , Netherlands , Nigeria , Oman , Saudi Arabia , Sierra Leone , Singapore , Sudan , TANZANIA, UNITED REPUBLIC OF , United Arab Emirates , Zambia

Output

Number of Outlets	6
Receptacle Style	UK BS1363 plug

Input

Nominal Input Voltage	230V
Input Power	0 W
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	British BS1363A
Maximum Line Current per phase	13.0 A
Cord Length	2.44 meters
Maximum Input Current	0 A

Surge Protection and Filtering

Surge energy rating	2030 joules
EP Joule Rating	2350 joules
EMI/RFI Noise rejection (100 kHz to 10 MHz)	50.0 dB
Peak Current Normal Mode	26 kA
Peak Current Common Mode	48.0 kA

NM Surge Response Time (ns)	0.0 ns
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines)
Data Lines Protected(multi-line only)	1-4 RJ11 / 3-6 RJ45
Let Through Voltage Rating	700

Physical

Net Weight	1.02 kg
Maximum Height	305.0 mm
Maximum Width	122.0 mm
Maximum Depth	42.0 mm
Shipping Weight	1.06 kg
Shipping Height	311.0 mm
Shipping Width	211.0 mm
Shipping Depth	52.0 mm
Master Carton Units	12.0
Master Carton Weight	30.0 lbs
SCC Codes	1073130422378 5
Color	Charcoal
Units per Pallet	120.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters

Conformance

Approvals	CE
Standard warranty	5 years (all other countries) , Lifetime (European Union countries only)
Equipment protection policy	Lifetime : 50000 GBP , Lifetime : 75000 Euros
UL 1449 TVSS Rating	--