



Overview

Model Name	APC Smart-UPS C 3000VA Rack mount LCD 230V
Includes	CD with software , Documentation CD , Installation guide , Rack Mounting brackets , USB cable
Standard Lead Time	Usually Ships within 2 Weeks
Product Distribution	Afghanistan , Algeria , Angola , Argentina , Armenia , Australia , Azerbaijan , Bahrain , Bangladesh , Belarus , Benin , Bhutan , Bolivia , Botswana , Brunei Darussalam , Burkina Faso , Burundi , Cambodia , Cameroon , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , <![CDATA[Cote D'Ivoire]]> , Djibouti , East Timor , Egypt , Equatorial Guinea , Eritrea , Ethiopia , Falkland Islands (Malvinas) , Gabon , Gambia , Georgia , Ghana , Guadeloupe , Guinea , French Guiana , Hong Kong , Indonesia , Iran (Islamic Republic Of) , Iraq , Israel , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Malaysia , Mali , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , New Zealand , Niger , Nigeria , Oman , Pakistan , Papua New Guinea , Paraguay , Peru , Philippines , Qatar , Reunion , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Somalia , South Africa , Sri Lanka , Sudan , Suriname , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	2100 Watts / 3000 VA
Max Configurable Power (Watts)	2100 Watts / 3000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Sine wave
Output Connections	(1) IEC 320 C19 (Battery Backup) , (2) IEC Jumpers (Battery Backup) , (8) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20
Input voltage range for main operations	180 - 287 V

Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 hour(s)
Replacement Battery	APCRBC151
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
Available SmartSlot™ Interface Quantity	0
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

Surge Protection and Filtering

Surge energy rating	300 joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	89.0 mm
Maximum Width	480.0 mm
Maximum Depth	670.0 mm
Rack Height	2 U
Net Weight	41.0 kg
Shipping Weight	50.9 kg
Shipping Height	254.0 mm
Shipping Width	600.0 mm
Shipping Depth	980.0 mm
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	16.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	42.000 dB
Online Thermal Dissipation	81.000 BTU/hr

Conformance

Approvals	C-tick , CE , EAC , GOST , GS Mark , IRAM , SABS , VDE
-----------	--

Standard warranty	2 years repair or replace
Equipment protection policy	Lifetime : \$150000

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
