



Info

- Core Line for ordinary duty in power chain applications


Technical data

- Classification**
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable
- Core identification code**
Black with white numbers acc. to VDE 0293-1
- Specific insulation resistance**
> 20 GOhm x cm
- Conductor stranding**
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
- Minimum bending radius**
For flexible use:
7.5 x outer diameter
Fixed installation: 4 x outer diameter
- Nominal voltage**
U₀/U: 300/500 V
- Test voltage**
4000 V
- Protective conductor**
G = with GN-YE protective conductor
X = without protective conductor
- Temperature range**
Flexing: 0°C to +70°C
Fixed installation: -40°C to +70°C

ÖLFLEX® CLASSIC FD 810

PVC-insulated, numbered, PVC sheath

LAPP KABEL STUTTGART ÖLFLEX® FD CLASSIC 810 CE



Benefits

- Well-proven and reliable
- Cost-effective solution

Application range

- In power chains or moving machine parts
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering
- Assembly lines, production lines, in all kinds of machines
- Plant engineering

Product features

- Low-adhesive surface
- Flame-retardant according IEC 60332-1-2
- In damp or wet interiors
- Designed for 2 up to 8 million bending/unbending cycles in power chain applications.
- Only for outdoor use within the indicated operating temperature range, with UV-protection

Norm references / Approvals

- Core based on VDE 0245/0285
- Outer sheath based on VDE 0245/0285
- For travel distances up to 10 m.
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

Product make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- Non-woven wrapping
- PVC outer sheath, grey (RAL 7001)

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0026100	2 X 0.5	5.3	10.0	40
0026101	3 G 0.5	5.7	15.0	48
0026102	4 G 0.5	6.3	19.2	58
0026103	5 G 0.5	6.8	24.0	67
0026104	7 G 0.5	8.0	34.0	88
0026105	12 G 0.5	9.5	58.0	136
0026106	18 G 0.5	11.4	86.4	195
0026107	25 G 0.5	13.7	120.0	274
0026108	30 G 0.5	14.3	144.0	312
0026109	34 G 0.5	15.6	164.0	359
0026110	50 G 0.5	18.5	240.0	515
0026119	2 X 0.75	5.7	15.0	49
0026120	3 G 0.75	6.2	22.0	60
0026121	4 G 0.75	6.8	29.0	73
0026122	5 G 0.75	7.4	37.0	86
0026123	7 G 0.75	8.9	51.0	117
0026124	12 G 0.75	10.6	87.0	181
0026125	16 G 0.75	12.0	116.0	234
0026126	18 G 0.75	12.7	130.0	259
0026127	25 G 0.75	15.2	181.0	363
0026130	2 X 1.0	6.1	19.0	58
0026131	3 G 1.0	6.6	29.0	72
0026132	4 G 1.0	7.3	39.0	88
0026133	5 G 1.0	8.0	48.0	104
0026134	7 G 1.0	9.6	67.0	142
0026135	12 G 1.0	11.4	115.0	221
0026136	14 G 1.0	12.3	134.4	258
0026137	16 G 1.0	13.0	153.0	287
0026138	18 G 1.0	13.9	173.0	324
0026139	25 G 1.0	16.4	240.0	445
0026140	26 G 1.0	16.4	249.6	459
0026141	34 G 1.0	18.9	326.4	595

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0026142	41 G 1.0	20.6	394.0	712
0026143	50 G 1.0	22.3	480.0	854
0026144	65 G 1.0	25.4	624.0	1097
0026149	2 X 1.5	6.8	29.0	74
0026150	3 G 1.5	7.4	43.2	93
0026151	4 G 1.5	8.1	58.0	114
0026152	5 G 1.5	9.1	72.0	139
0026153	7 G 1.5	10.9	101.0	189
0026154	12 G 1.5	12.9	173.0	295
0026156	18 G 1.5	15.6	259.0	429
0026157	25 G 1.5	18.6	360.0	597
0026158	26 G 1.5	18.6	374.4	615
0026159	34 G 1.5	21.1	489.6	783
0026160	41 G 1.5	23.0	613.0	936
0026161	42 G 1.5	23.0	629.0	954
0026162	50 G 1.5	25.0	720.0	1134
0026170	3 G 2.5	9.0	72.0	145
0026171	4 G 2.5	10.0	96.0	179
0026172	5 G 2.5	11.2	120.0	218
0026173	7 G 2.5	13.6	168.0	303
0026174	12 G 2.5	16.0	288.0	473
0026175	14 G 2.5	17.2	336.0	548
0026180	3 G 4	10.6	120.0	214
0026181	4 G 4	11.7	160.0	266
0026182	5 G 4	13.1	200.0	325
0026183	4 G 6	13.9	223.0	396
0026184	5 G 6	15.5	288.0	484
0026185	4 G 10	17.6	384.0	644
0026186	5 G 10	19.6	480.0	785
0026187	4 G 16	21.0	615.0	922
0026188	5 G 16	23.6	768.0	1133

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® FD 891 refer to page 114

Accessories

- SILVYN® CHAIN cable protection and guiding systems