



## ÖLFLEX® CLASSIC FD 810 P

PVC-insulated, numbered, PUR sheath

LAPP KABEL STUÏGART ÖLFLEX® FD CLASSIC 810 P CE

LAPP KABEL STUÏGART ÖLFLEX® FD CLASSIC 810 P CE

### Benefits

- Well-proven and reliable
- Various applications

### Application range

- In power chains or moving machine parts
- Particularly in wet areas of machine tools and transfer lines
- Mechanical engineering
- Suitable for use in measuring, control and regulating circuits
- Power circuits for electrical equipments used in automation engineering

### Product features

- Low-adhesive surface
- Oil-resistant
- Flame-retardant according to IEC 60332.1.2
- In dry, damp or wet interiors with normal mechanical stress conditions
- Designed for 2 up to 8 million bending/unbending cycles in power chain applications.

### Norm references / Approvals

- Core based on VDE 0245/0285
- Outer sheath based on VDE 0245/0285
- For travel distances up to 10 m.
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

### Product make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in short lay lengths
- Non-woven wrapping
- PUR outer sheath, grey (RAL 7001)

**Info**

- Core Line for ordinary duty in power chain applications

### Technical data

- Classification**  
ETIM 5.0 Class-ID: EC000104  
ETIM 5.0 Class-Description: Control cable
- Core identification code**  
Black with white numbers acc. to VDE 0293-1
- Specific insulation resistance**  
> 20 GOhm x cm
- Conductor stranding**  
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
- Minimum bending radius**  
For flexible use:  
7.5 x outer diameter  
Fixed installation: 4 x outer diameter
- Nominal voltage**  
U<sub>0</sub>/U: 300/500 V
- Test voltage**  
4000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
Flexing: -5°C to +70°C  
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0026300	2 X 0.5	5.3	10.0	36
0026301	3 G 0.5	5.7	15.0	44
0026302	4 G 0.5	6.3	19.0	53
0026303	5 G 0.5	6.8	24.0	62
0026304	7 G 0.5	8.0	34.0	82
0026305	12 G 0.5	9.5	58.0	129
0026306	18 G 0.5	11.4	86.4	185
0026319	2 X 0.75	5.7	15.0	44
0026320	3 G 0.75	6.2	22.0	55
0026321	4 G 0.75	6.8	29.0	67
0026322	5 G 0.75	7.4	37.0	80
0026323	7 G 0.75	8.9	51.0	109
0026324	12 G 0.75	10.6	87.0	172
0026326	18 G 0.75	12.7	130.0	247
0026327	25 G 0.75	15.2	181.0	346
0026330	2 X 1.0	6.1	20.0	52
0026331	3 G 1.0	6.6	29.0	66
0026332	4 G 1.0	7.3	39.0	82
0026333	5 G 1.0	8.0	48.0	97
0026334	7 G 1.0	9.6	67.0	117
0026335	12 G 1.0	11.4	115.0	211
0026338	18 G 1.0	13.9	173.0	310
0026339	25 G 1.0	16.4	240.0	426
0026341	34 G 1.0	18.9	326.4	571
0026342	41 G 1.0	20.6	394.0	684
0026343	50 G 1.0	22.3	480.0	822
0026344	65 G 1.0	25.4	624.0	1058

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0026349	2 X 1.5	6.8	29.0	68
0026350	3 G 1.5	7.4	43.2	86
0026351	4 G 1.5	8.1	58.0	106
0026352	5 G 1.5	9.1	72.0	131
0026353	7 G 1.5	10.9	101.0	178
0026354	12 G 1.5	12.9	173.0	281
0026355	16 G 1.5	14.6	230.0	365
0026356	18 G 1.5	15.6	259.0	411
0026357	25 G 1.5	18.6	360.0	571
0026359	34 G 1.5	21.1	489.6	753
0026361	42 G 1.5	23.0	629.0	919
0026362	50 G 1.5	25.0	720.0	1093
0026370	3 G 2.5	9.0	72.0	135
0026371	4 G 2.5	10.0	96.0	168
0026372	5 G 2.5	11.2	120.0	206
0026373	7 G 2.5	13.6	168.0	286
0026374	12 G 2.5	16.0	288.0	453
0026375	14 G 2.5	17.2	336.0	525
0026381	4 G 4	11.7	160.0	252
0026382	5 G 4	13.1	200.0	309
0029200	1 G 6	6.4	60.0	84
0026383	4 G 6	13.9	230.0	377
0029210	1 G 10	7.7	100.0	141
0026385	4 G 10	17.6	384.0	614
0026386	5 G 10	19.6	480.0	751
0029220	1 G 16	9.2	160.0	198
0026387	4 G 16	21.0	615.0	851

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
 Photographs are not to scale and do not represent detailed images of the respective products.

### Similar products

- ÖLFLEX® FD 855 P refer to page 120

### Accessories

- SILVYN® CHAIN cable protection and guiding systems