



ÖLFLEX® ROBUST FD C

Screened, TPE-insulated, numbered, TPE inner and outer sheath



LAPP KABEL STUTTGART ÖLFLEX® FD ROBUST C

Benefits

- Well-proven and reliable
- Various applications
- Suitable for all weather conditions
- EMC-compliant
- For indoor and outdoor use

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Particularly in wet areas of machine tools and transfer lines
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- Resistant to contact with plant, animal or synthetic-based organic oils, greases, waxes and the related emulsions
- Assembly lines, production lines, in all kinds of machines

Product features

- Hydrolysis-resistant to warm and hot water
- Low-adhesive surface
- Highly resistant to oil and chemicals
- In dry, damp or wet interiors with normal mechanical stress conditions
- Designed for 5 up to 10 million bending/unbending cycles in the power chain.

Norm references / Approvals

- Based on VDE 0250 / 0285
- For travel distances up to 100 m (horizontal)
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

Product make-up

- Extra-fine wire, tinned copper strands
- Core insulation: TPE
- Cores twisted together in extremely short lay lengths
- Non-woven wrapping
- Inner sheath made of TPE
- Tinned-copper braiding
- Robust outer sheath made of special halogen-free TPE, black (RAL 9005)



Info

- Good chemical resistance
- Extended Line for heavy duty in power chain applications

Technical data



Classification

ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable



Core identification code

Black cores with printed white numbers (VDE 0293-1)



Specific insulation resistance

> 20 GOhm x cm



Conductor stranding

Extra-fine wire acc. to VDE 0295, class 6 / IEC 60228 class 6



Minimum bending radius

For flexible use:
7.5 x cable diameter (at temperatures < 70 °C)
10 x cable diameter (at a max. temperature of 105 °C)
Fixed installation: 4 x Outer diameter



Nominal voltage

U₀/U: 300/500 V



Test voltage

4000 V



Protective conductor

G = with GN-YE protective conductor
X = without protective conductor



Temperature range

Flexing: -40 °C to +105 °C
Fixed installation: -50 °C to +105 °C
Short-term: up to +120 °C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0026701	3 G 0.75	9.1	49.6	110
0026702	4 G 0.75	10.1	60.9	137
0026703	5 G 0.75	10.8	72.8	160
0026704	7 G 0.75	12.6	107.2	238
0026705	12 G 0.75	15.0	151.5	312
0026706	18 G 0.75	17.7	205.5	448
0026707	25 G 0.75	21.7	299.1	657
0026709	3 G 1.0	9.8	61.1	125
0026716	7 G 1.0	13.9	132.3	278
0026717	12 G 1.0	16.1	189.1	370
0026721	3 G 1.5	10.9	79.8	163
0026722	4 G 1.5	12.1	99.2	210
0026723	5 G 1.5	13.6	129.7	264
0026724	7 G 1.5	15.8	175.2	370
0026725	12 G 1.5	18.4	257.1	498
0026726	18 G 1.5	22.1	378.9	749
0026727	25 G 1.5	27.1	555.5	1042
0026731	4 G 2.5	14.4	161.5	307
0026732	5 G 2.5	15.5	188.3	361
0026733	7 G 2.5	18.3	252.6	512
0026734	12 G 2.5	21.9	406.5	730
0026741	4 G 4	16.2	227.3	412
0026751	4 G 6	17.2	306.7	519
0026761	4 G 10	23.3	513.6	853
0026771	4 G 16	27.2	809.6	1273

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® PETRO FD 865 CP refer to page 122

Accessories

- SKINTOP® MS-M BRUSH refer to page 675
- SILVYN® CHAIN cable protection and guiding systems