



Info

- Core Line for ordinary duty in power chain applications

Technical data

Classification
ETIM 5.0 Class-ID: EC000104
ETIM 5.0 Class-Description: Control cable

Core identification code
Black with white numbers acc. to VDE 0293-1

Specific insulation resistance
> 20 GOhm x cm

Conductor stranding
Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

Minimum bending radius
For flexible use:
7.5 x outer diameter
Fixed installation: 4 x outer diameter

Nominal voltage
IEC: 300/500 V
UL/CSA: 600 V

Test voltage
4000 V

Protective conductor
G = with GN-YE protective conductor
X = without protective conductor

Temperature range
Flexing: -5°C to +80°C
Fixed installation: -40°C to +80°C



ÖLFLEX® FD 891 P

PVC-insulated, numbered, PUR sheath, approved

Benefits

- Multi-standard = fewer part varieties = cost savings
- Protection against water and dirt

Application range

- In power chains or moving machine parts
- Plant engineering
- Machine tools

Product features

- Abrasion and cut-resistant
- Oil-resistant
- Low-adhesive surface
- Flame-retardant according to IEC 60332-1-2 & CSA FT1
- Designed for 2 up to 8 million bending/unbending cycles in power chain applications.

Norm references / Approvals

- UL rec. AWM Style 20234
- CRU AWM II A/B FT 1
- For travel distances up to 10 m.
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3
- UL File Nr. E63634

Product make-up

- Extra-fine wire strand made of bare copper wires (class 6)
- Core insulation: PVC
- Cores twisted in layers in short lay lengths
- Non-woven wrapping
- PUR outer sheath, black (RAL 9005)

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
1028752	2 X 0.5	6.5	9.6	46
1028007	7 G 0.5	9.6	33.6	118
1028103	3 G 0.75	7.3	21.6	66
1028104	4 G 0.75	8.0	28.8	82
1028105	5 G 0.75	8.7	36.0	101
1028107	7 G 0.75	10.7	50.4	142
1028112	12 G 0.75	11.7	86.4	196
1028118	18 G 0.75	13.9	129.6	282
1028125	25 G 0.75	16.6	180.0	404
1028134	34 G 0.75	18.9	244.8	541
1028150	50 G 0.75	22.5	360.0	738
1028303	3 G 1.5	8.4	43.2	98
1028304	4 G 1.5	9.3	57.6	125
1028305	5 G 1.5	10.1	72.0	155
1028307	7 G 1.5	11.9	100.8	221
1028312	12 G 1.5	13.9	172.8	318
1028318	18 G 1.5	16.9	259.2	484
1028325	25 G 1.5	20.1	360.0	671
1028334	34 G 1.5	23.1	489.6	910
1028952	2 X 2.5	8.9	48.0	102
1028403	3 G 2.5	9.3	72.0	134
1028404	4 G 2.5	10.3	96.0	173
1028405	5 G 2.5	11.3	120.0	217
1028407	7 G 2.5	13.4	168.0	312
1028412	12 G 2.5	15.8	288.0	460
1028503	3 G 4	10.9	115.2	197
1028504	4 G 4	12.1	153.6	257
1028507	7 G 4	16.1	268.8	471
1028604	4 G 6	13.7	230.4	363
1028614	4 G 10	17.9	384.0	605
1028624	4 G 16	23.4	614.4	973
1028634	4 G 25	27.6	960.0	1437

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
DESINA® is a registered trademark of the German Machine Tool Builders' Association
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® FD 855 P refer to page 120

Accessories

- SILVYN® CHAIN cable protection and guiding systems