

ÖLFLEX® TRAIN 310 TW-P 300V

Multi-core cable according to EN 50306-4 1P type MM for high requirements in railway applications

ÖLFLEX® TRAIN 310 TW-P 300V - control cable according to EN 50306-4 1P type MM, 300/500V for rail vehicles/trains, EN 45545: HL1-HL3, NF F 16-101: C/F0

Info

Meets EN 50306-4 class P, type MM and EN 45545-2

High temperature resistance: -45 °C to +125 °C

Highly oil- and fuel-resistant

LAPP KABEL STUTTGART ÖLFLEX® TRAIN 310 TW-P 300V EN 50306-4 1P MM



CE



UV-resistant



Temperature-resistant



Space requirement



Oil-resistant



Mechanical resistance



Halogen-free



Good chemical resistance



Rail

Last Update (17.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® TRAIN 310 TW-P 300V



Flame-retardant



Cold-resistant

Benefits

- Reduced insulation wall thickness, therefore a space-saving installation
- Good chemical resistance
- Resistant to mechanical influences in harsh environmental conditions
- Extended temperature range
- Reduced flame spreading for protection against damage to persons and property in the event of a fire

Application range

- For use in railway vehicles and buses, for fixed and protected installation and applications where limited movement is to be expected
- Suitable for control and monitoring circuits as well as locking circuits and internal wiring of equipment in trains and locomotives
- Can also be used in oily environments and areas with increased ambient temperature

Product features

- Fire behaviour in accordance with EN/IEC:
 - Halogen-free according to EN 60754-1
 - No corrosive gases according to EN 60754-2
 - No fluorine according to EN 60684-2
 - No toxic gases according to EN 50305
 - Low smoke density according to EN 61034-2
 - Flame-retardant according to EN 60332-1-2
 - No flame propagation according to EN 60332-3-24 / EN 60332-3-25 / EN 50305
- Fire behaviour in accordance with NF:
 - Toxicity of combustion gases according to NF X 70-100
 - Low smoke density according to NF X 10-702
 - No flame propagation according to NF C 32-070, cat. C1 and C2
- Chemical properties:
 - Oil-resistant according to EN 50306
 - Fuel-resistant according to EN 50306
 - Acid-resistant according to EN 50306
 - Alkali-resistant according to EN 50306
 - Ozone-resistant according to EN 50306

Norm references / approvals

- EN 50306-4 class P, type MM
- EN 45545-2 HL1, HL2, HL3
- NF F 16-101 - classification: C / F0
(flame propagation / smoke)

Design

- Tin-plated copper strand, 19- or 37-wire, SRC (Special Round Conductor)
- Insulation: Electron beam cross-linked polymer compound according to EN 50306
- Core colour: White with black numbers
- Sheath: Electron beam cross-linked polymer-compound S2 according to EN 50306
- Sheath colour: Black

ÖLFLEX® TRAIN 310 TW-P 300V

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Core identification code:	White with black numbers
Conductor design:	SRC (special round conductor) 19- or 37-wire according to EN 50306-1
Minimum bending radius:	Fixed installation: ≤ 12 mm: 4 x OD / 3 x OD* > 12 mm: 5 x OD / 4 x OD* * for careful bending, once at connecting terminal Occasional flexing: ≤ 12 mm: 5 x OD > 12 mm: 6 x OD (OD = outer diameter)
Nominal voltage:	U ₀ /U AC 300/500 V U _m AC 550 V V ₀ DC 410 V Fixed installation: U ₀ /U AC 0.6/1 kV U _m AC 1.2 kV V ₀ DC 0.9 kV
Test voltage:	3,5 kV AC; 8,4 kV DC
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Fixed installation: -45°C to +125°C (20,000 h) Occasional flexing: -35°C to +105°C Short circuit: +160°C (5s)

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Packaging: Ring ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred packaging (e.g. 1 x 500 m drum or 5 x 100 m rings)

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**ÖLFLEX® TRAIN 310 TW-P 300V**

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
15310000	4 X 0.5	4.6	19.2	41.7
15310001	7 X 0.5	5.4	33.6	63.51
15310002	13 X 0.5	7.8	62.4	120.45
15310003	19 X 0.5	8.6	91.2	157.19
15310004	37 X 0.5	11.4	177.6	285.06
15310005	4 X 0.75	5.1	28.8	55.29
15310006	7 X 0.75	6	50.4	83.91
15310007	13 X 0.75	8.7	93.6	161.87
15310008	19 X 0.75	9.6	136.8	213.91
15310009	37 X 0.75	12.8	266.4	392.13
15310011	4 X 1	5.4	38.4	67.78
15310012	7 X 1	6.5	67.2	105.98
15310013	13 X 1	9.3	124.8	200.43
15310014	19 X 1	10.4	182.4	267.49
15310015	37 X 1	13.9	355.2	497.75
15310016	4 X 1.5	6.5	57.6	98.42
15310017	7 X 1.5	8.2	108	170.32
15310018	13 X 1.5	11.3	187.2	294.53
15310019	19 X 1.5	12.6	273.6	395.64
15310020	37 X 1.5	17	532.8	727.91
15310021	2 X 2.5	7.2	49.2	106.11
15310022	3 X 2.5	7.6	73.8	130.81
15310023	4 X 2.5	8.4	98.4	165.38

Last Update (17.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16