

PUR-YELLOW PVC-inner sheath, high abrasion, coolant resistant, meter marking



Technical data

- Special-PVC/PUR control cable adapted to DIN VDE 0285-525-1 / DIN EN 50525-1
- **Temperature range**
flexing -15°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage** U₀/U 300/500 V
- **Test voltage** 3000 V
- **Breakdown voltage** min. 6000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special PVC compound type T12 adapted to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification to DIN VDE 0293-308
- up to 5 cores coloured
- from 6 cores, black with continuous white numbering
- GN-YE conductor, 3 cores and above
- Cores stranded in layers with optimal lay-length
- Inner sheath of PVC guarantees easy cable stripping
- Outer sheath of PUR compound type TMPU to DIN EN 50363-10-2
- Sheath colour yellow (RAL 1021)
also available in other colours on request
- with meter marking

Properties

- High flexibility at low temperature
- High abrasion resistance
- **Resistant to**
Oils and fats
Non-alcoholic fuels and kerosene
Atmospheric influences
UV-radiation
Oxygene and ozone
Microbes and rotting
Sea and waste water
Vibrations
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

Note

- G = with green-yellow conductor
x = without green-yellow conductor (OB).
- Art.no. 22212 = JB-version.
- Art.no. 22220 = JZ-version.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².

Application

Robust control cable with an outstanding resistance to oil and abrasion. Suitable for use in tool making and machine industries, steel works, on building sites and in the oil and coal industries. The cable can also be used for portable tools. etc. To be recommended if the cable comes into contact with chemical agents.

CE The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
22200	2 x 0,75	6,4	14,4	50,0	19	22212	4 G 1,5	9,0	58,0	135,0	16
22201	3 G 0,75	6,8	21,6	70,0	19	22220	4 G 1,5	9,7	58,0	135,0	16
22202	4 G 0,75	7,3	28,8	80,0	19	22213	5 G 1,5	11,2	72,0	158,0	16
22203	5 G 0,75	8,2	36,0	100,0	19	22214	7 G 1,5	9,2	101,0	221,0	16
22204	7 G 0,75	9,2	50,0	140,0	19	22215	2 x 2,5	9,6	48,0	150,0	14
22205	2 x 1	7,2	19,2	63,0	18	22216	3 G 2,5	11,0	72,0	173,0	14
22206	3 G 1	7,6	29,0	76,0	18	22217	4 G 2,5	12,0	96,0	203,0	14
22207	4 G 1	8,0	38,0	95,0	18	22218	5 G 2,5	13,7	120,0	253,0	14
22208	5 G 1	8,8	48,0	120,0	18	22219	7 G 2,5	9,0	168,0	356,0	14
22209	7 G 1	10,0	67,0	170,0	18	22221	4 G 4	14,6	153,6	310,0	12
22210	2 x 1,5	7,8	29,0	80,0	16	22222	5 G 4	14,8	192,0	370,0	12
22211	3 G 1,5	8,3	43,0	105,0	16	22233	4 G 35	33,0	1344,0	2100,0	2

Dimensions and specifications may be changed without prior notice. (RA02)