


Expanded ambient temperatures

Silicone cables (-50°C to +180°C)



# ÖLFLEX® HEAT 180 MS

Certified silicone cables for North America (AWM recognized)



**Info**

- MS = Multi-Standard  
For use in the USA and Canada
- UL AWM Style 4476 (150°C/600V)

**Benefits**

- Certified for the USA and Canada for export-oriented appliance and apparatus manufacturers
- Thicker cable design meets the requirements of the FT-1 flame test and also approved for the external interconnection of apparatuses and appliances
- Flexibility simplifies installation where space is limited
- Possesses insulating properties after combustion due to remaining SiO<sub>2</sub> ash on the conductor

**Application range**

- Areas with high ambient temperatures where insulating and sheath materials of conventional cables will embrittle after a short while
- Typical fields of application
  - Steel, ceramic and iron works
  - Bakery equipment and industrial furnaces
  - Electric motor industry
  - Sauna/solarium construction
  - Thermal and heating elements
  - Lighting technology
  - Ventilator engineering
  - Air-conditioning technology
  - Galvanisation technology

**Product features**

- Metric flexible conductor design
- Halogen-free and flame-retardant (IEC 60332-1-2)
- Good hydrolysis and UV-resistance
- Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances

**Norm references / Approvals**

- UL AWM 4476 and cUL AWM II A/B Construction B, External interconnection

**Product make-up**

- Fine-wire, tinned-copper conductor
- Silicone-based core insulation
- Cores twisted together
- Silicone-based outer sheath, colour black

**Technical data**

- Classification**  
ETIM 5.0 Class-ID: EC001578  
ETIM 5.0 Class-Description: Flexible cable
- Core identification code**  
Colours according to VDE 0293-308, refer to Appendix T9  
From 6 cores: black with white numbers
- Conductor stranding**  
Fine wire according to VDE 0295, class 5/IEC 60228 class 5  
(Refer to Appendix T16 for the matching US conductor sizes in AWG standard)
- Minimum bending radius**  
Occasional flexing: 15 x outer diameter  
Fixed installation: 4 x outer diameter
- Nominal voltage**  
U<sub>0</sub>/U: 300/500 V  
Working voltage UL: 600 V
- Test voltage**  
2000 V
- Protective conductor**  
G = with GN-YE protective conductor  
X = without protective conductor
- Temperature range**  
According to VDE: -50 °C to +180 °C  
Normatively acc. UL Style: up to +150 °C (adequate ventilation required)

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® HEAT 180 MS</b>				
0046600	2 X 0.5	7.4	9.8	72
0046601	3 G 0.5	7.8	14.7	83
00466023	4 G 0.5	8.5	19.6	99
00466033	5 G 0.5	9.2	24.5	119
0046604	7 G 0.5	9.9	34.3	142
0046612	2 X 1	8.2	19.2	93
0046613	3 G 1	8.7	28.8	110
00466143	4 G 1	9.4	38.4	133
00466153	5 G 1	10.3	48.0	160
0046616	7 G 1	11.1	67.2	195
0046617	12 G 1	14.9	115.2	345
0046618	2 X 1.5	8.8	28.8	113
0046619	3 G 1.5	9.3	43.2	135
00466203	4 G 1.5	10.1	57.6	165

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
00466213	5 G 1.5	11.1	72.0	200
0046622	7 G 1.5	12.0	100.8	246
0046623	12 G 1.5	16.1	172.8	437
0046625	18 G 1.5	18.8	259.2	613
0046626	25 G 1.5	22.9	360.0	904
0046628	2 X 2.5	9.6	48.0	146
0046629	3 G 2.5	10.2	72.0	178
00466303	4 G 2.5	11.1	96.0	220
00466313	5 G 2.5	12.2	120.0	269
0046633	3 G 4	11.5	115.2	246
00466343	4 G 4	12.6	153.6	307
00466353	5 G 4	14.2	192.0	389
0046636	3 G 6	14.9	172.8	396
00466373	4 G 6	16.4	230.4	495
00466383	5 G 6	18.0	288.0	608

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- ÖLFLEX® HEAT 180 C MS refer to page 169