



UNITRONIC® LiYD11Y

Data transmission cable with copper wrapping and PUR outer sheath

LAPP KABEL STUÏGART UNITRONIC LiYD11Y

■ Benefits

- Increased durability under harsh conditions thanks to robust PUR outer sheath
- Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
- Overall screening which prevents external electrical interference and guarantees precise pulse transmission

■ Application range

- Intended for use in industrial environments, where cables should have excellent mechanical and chemical resistance.
- Screened cables with small dimensions are suitable for use in computer systems, instrumentation technology, office equipment, balances.
- Can be used in dry or damp rooms
- Outdoor use is possible within the indicated operating temperature range

■ Product features

- PUR outer sheath, tear and notch-resistant, resistant to mineral oils and abrasion
- Low-adhesive surface
- Good UV-resistance
- Flame-retardant according IEC 60332-1-2
- Spiral versions are also available except for the 7-core version

■ Norm references / Approvals

- Based on VDE 0812

■ Product make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation made of PVC
- Screening: wrapped with bare copper wires
- Outer sheath made of PUR
Outer sheath colour: black (RAL 9005)

■ Technical data

- Core identification code**
DIN 47100 without colour repetition, refer to Appendix T9
- Mutual capacitance**
C/C approx. 140 nF/km
C/S approx. 150 nF/km
- Peak operating voltage**
(not for power applications) 250 V
- Specific insulation resistance**
> 20 GOhm x cm
- Inductivity**
approx. 0.65 mH/km
- Conductor stranding**
Stranded, extra-fine wire
- Minimum bending radius**
Occasional flexing: 10 x outer diameter
Fixed installation: 6 x outer diameter
- Test voltage**
1200 V
- Temperature range**
Occasional flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYD11Y				
0033202	2 x 0.14	4.1	9.6	20
0033203	3 x 0.14	4.3	11.0	25
0033204	4 x 0.14	4.5	12.0	27
0033205	5 x 0.14	4.8	14.4	33
0033206	6 x 0.14	5.5	17.6	38
0033207	7 x 0.14	5.9	21.5	41
0033212	12 x 0.14	7.2	33.2	62
0033218	18 x 0.14	8.0	44.2	83
0033302	2 x 0.25	4.7	11.8	25
0033303	3 x 0.25	5.3	15.6	31
0033304	4 x 0.25	5.6	18.2	36
0033305	5 x 0.25	6.0	21.4	42
0033306	6 x 0.25	6.8	26.1	49
0033312	12 x 0.25	8.4	48.1	81

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

■ Similar products

- UNITRONIC® SPIRAL refer to page 227

■ Accessories

- Multipurpose shears A and B refer to page 907
- UNIVERSAL STRIP stripping and cutting tool refer to page 910
- DATA STRIP stripping tool refer to page 911