



UNITRONIC® FD

Highly flexible data transmission cable with PVC outer sheath for power chain use

LAPP KABEL STUIGART UNITRONIC® FD



Benefits

- Well-proven and reliable
- Optimized cable construction for power chain use
- Cost-effective solution

Application range

- Automated production processes require data transmission cables that offer high flexibility and durability
- Suitable for use in measuring, control and regulating circuits
- Assembly lines, production lines, in all kinds of machines

Product features

- Low-adhesive surface
- Flame-retardant according IEC 60332-1-2
- Designed for 2 up to 8 million bending/unbending cycles in power chain applications.

Norm references / Approvals

- Based on VDE 0812
- For travel distances up to 10 m.
- For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

Product make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation made of PVC
- Non-woven wrapping
- Outer sheath made of PVC
Outer sheath colour: grey (RAL 7001)

Technical data

- Core identification code**
DIN 47100, refer to Appendix T9
- Mutual capacitance**
C/C: approx. 100 nF/km
- Peak operating voltage**
(not for power applications)
350 V
- Specific insulation resistance**
> 20 GOhm x cm
- Inductivity**
approx. 0.65 mH/km
- Conductor stranding**
Stranded, extra-fine wire
- Minimum bending radius**
Flexing: 5 x outer diameter
Fixed installation: 3 x outer diameter
- Test voltage**
1500 V
- Temperature range**
Flexing: -5°C to +70°C
Fixed installation: -40°C to +80°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® FD				
0027841	3 x 0.14	3.9	4.2	26
0027842	4 x 0.14	4.2	5.6	31
0027843	5 x 0.14	4.5	7.0	35
0027844	7 x 0.14	5.1	9.8	50
0027845	10 x 0.14	6.1	14.0	63
0027846	14 x 0.14	6.2	19.6	77
0027847	18 x 0.14	6.8	25.2	91
0027848	25 x 0.14	8.3	35.0	125
0027855	2 x 0.25	4.3	5.0	27
0027856	3 x 0.25	4.5	7.5	33
0027857	4 x 0.25	4.9	10.0	40
0027858	5 x 0.25	5.3	12.5	51
0027859	7 x 0.25	6.1	17.5	51
0027860	10 x 0.25	7.4	25.0	84
0027861	14 x 0.25	7.5	35.0	108
0027863	18 x 0.25	8.5	45.0	130
0027865	25 x 0.25	10.4	62.5	178
0027870	2 x 0.34	4.7	6.8	30
0027871	3 x 0.34	5.0	10.2	43
0027872	4 x 0.34	5.4	13.6	57
0027873	5 x 0.34	5.9	17.0	65
0027874	7 x 0.34	6.8	23.8	85
0027875	10 x 0.34	8.5	34.0	117
0027876	14 x 0.34	8.6	47.6	151
0027877	18 x 0.34	9.7	61.2	182
0027878	25 x 0.34	11.9	85.0	250

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CLASSIC FD 810 refer to page 107
- UNITRONIC® FD CY refer to page 271
- UNITRONIC® FD P plus refer to page 272

Accessories

- SILVYN® CHAIN
- DATA STRIP stripping tool refer to page 911