

# ADC Structured Cabling Solutions

## Category 5e UTP Cable

Issue 2



This Category 5e UTP 4-pair Cable is an unshielded cable, designed to provide Category 5e Enhanced Link and Channel performance with internationally defined physical and electrical performance up to 100MHz.

The insulation on the 4 pairs for twisted copper is colour coded: Blue, Orange, Green, and Brown.

### Specifications

Conductor: .....0.5mm Dia. (24 AWG) copper  
Insulation: .....Polyethylene  
Jacket: .....PVC  
Outside diameter: .....5.0 mm nominal  
Complies with : ISO/IEC 11801  
TIA/EIA 568-B.2  
IEC60332.1

#### Mechanical:

Minimum bending radius:  
- During installation .....50mm  
- After installation.....25mm  
Maximum pulling tension: .....108N (11kg)  
Box mass, full, nominal: .....11kg

#### Thermal:

Operation: .....-15°C to 70°C  
Installation: .....5°C to 40°C  
Flame rating: .....CM

#### Electrical:

Conductor DC resistance @ 20°C (max): .....9.38Ω/100m  
DC resistance unbalances (max): .....5%  
Mutual capacitance @ 20°C (max): .....5.6nF/100m  
Worst case cable skew.....45ns/100m  
NVP setting.....70%

SPEC SHEET



[www.adc.com/in](http://www.adc.com/in) • 1800 425 8232

# ADC Structured Cabling Solutions

## Category 5e UTP Cable

Operating voltage (max): .....300Vdc

Freq	Attenuation	Pr-Pr NEXT	Power Sum NEXT	Return Loss	Pr-Pr ELFEXT	Power Sum ELFEXT	Pr-Pr ACR	Power Sum ACR
(MHz)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)
1.00	1.95	77.2	77.0	31.5	74.7	76.9	75.2	75.0
4.00	3.62	71.0	68.7	28.7	64.7	64.7	67.4	65.1
10.00	6.11	61.4	61.8	32.1	55.9	55.7	55.3	55.6
16.00	7.89	60.4	66.3	32.1	51.7	51.7	52.5	58.4
20.00	8.77	55.5	64.8	28.9	50.0	49.7	46.7	56.1
31.25	11.09	52.4	53.8	28.8	46.1	45.1	41.3	42.7
62.50	15.96	52.4	52.4	25.2	39.1	38.9	36.5	36.5
100.00	20.41	47.0	46.2	26.8	31.8	34.2	26.6	25.8
200.00	29.73	39.1	41.8	19.1	25.1	28.8	9.4	12.0
250.00	33.53	38.4	42.6	19.3	25.3	31.1	4.9	9.1
300.00	36.74	36.1	34.8	16.9	18.9	18.3	-0.7	-2.0
350.00	39.89	32.3	33.0	15.8	17.7	15.8	-7.6	-6.9

Note: The above listed discrete frequency performance values are provided for engineering information only. Actual compliance testing is based on swept frequency measurements. The spec values are based on TIA.EIA 568-B.2 specifications.

### Ordering Information

Description	Quantity	Colour	Product No.
Category 5e 4-pair Cable, Solid UTP	305m reel	Grey	6499 1 028-01
Category 5e 4-pair Cable, Solid UTP	305m reel	Blue	6499 1 028-02

\*KRONE Communications Ltd. is now ADC India Communications Ltd.

SPEC SHEET



#### www.adc.com/in

10C, II Phase Peenya Industrial Area  
Bangalore 560 058  
Sales Support: 1800 425 8232

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101  
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6499 1 028-XXIN / Issue 2 © 2010 ADC Telecommunications, Inc. All Rights Reserved.