



New

HITRONIC® FIRE



Info

- A/J-DQ(ZN)BH(SR)H or U-DQ(ZN)BH(SR)H
- Fire-resistant for at least 90 minutes in the event of fire*
- * Cable had been tested to withstand 180 min

Benefits

- Ensures that the fibres can still transmit data during and after a fire (according to IEC 60331-25)*
- Suitable for installation in underground tunnels where fire safety is critical
- Additional sheath protects the fibres for use in harsh environments
- Armouring provides excellent protection against high mechanical stress and rodents
- UV-resistant longitudinally and laterally watertight

Application range


- In industrial areas that use fire as a tool
- Highly combustible or fire-prone areas
- For indoor and outdoor use
- Methods of Deployment: empty plastic pipes, ducts and trays

Product features

- Fire behaviour:
 - Halogen-free (IEC 60754-1)
 - Flame-retardant (IEC 60332-3)
 - Low smoke density (IEC 61034-1/2)
 - Circuit integrity (IEC 60331-25); Optical fibre cables
- Central loose tube with up to 24 fibres
- Colour-coded fibres
- Longitudinal watertight
- Flame-retardant and halogen-free outer sheath

Product make-up

- Gel-filled loose tube
- Water-blocking reinforced glass yarn strain relief
- Corrugated steel tape armour
- LSZH inner and outer sheaths
- Colour: black (RAL 9005)



Technical data



Optical fibre type

Core material: glass
Cladding material: glass



Temperature range

Fixed installation: -30°C to +70°C



Permissible bending radius

Static: ≥ 15 x outer diameter
Dynamic: ≥ 20 x outer diameter



Permissible tensile force

Fixed installation: 1500 N
Short-term: 2200 N

Article number	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Multimode G 50 OM3					
27560304	HITRONIC® FIRE 4G 50/125 OM3	50/125 OM3	4	9.8	123
27560308	HITRONIC® FIRE 8G 50/125 OM3	50/125 OM3	8	9.8	123
27560312	HITRONIC® FIRE 12G 50/125 OM3	50/125 OM3	12	12.8	188
27560324	HITRONIC® FIRE 24G 50/125 OM3	50/125 OM3	24	12.8	188
Multimode G 50 OM2					
27560204	HITRONIC® FIRE 4G 50/125 OM2	50/125 OM2	4	9.8	123
27560208	HITRONIC® FIRE 8G 50/125 OM2	50/125 OM2	8	9.8	123
27560212	HITRONIC® FIRE 12G 50/125 OM2	50/125 OM2	12	12.8	188
27560224	HITRONIC® FIRE 24G 50/125 OM2	50/125 OM2	24	12.8	188
Multimode G 62.5 OM1					
27560104	HITRONIC® FIRE 4G 62.5/125 OM1	62.5/125 OM1	4	9.8	123
27560108	HITRONIC® FIRE 8G 62.5/125 OM1	62.5/125 OM1	8	9.8	123
27560112	HITRONIC® FIRE 12G 62.5/125 OM1	62.5/125 OM1	12	12.8	188
27560124	HITRONIC® FIRE 24G 62.5/125 OM1	62.5/125 OM1	24	12.8	188
Single-mode E 9 OS2					
27560904	HITRONIC® FIRE 4E 9/125 OS2	9/125 OS2	4	9.8	123
27560908	HITRONIC® FIRE 8E 9/125 OS2	9/125 OS2	8	9.8	123
27560912	HITRONIC® FIRE 12E 9/125 OS2	9/125 OS2	12	12.8	188
27560924	HITRONIC® FIRE 24E 9/125 OS2	9/125 OS2	24	12.8	188

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. The cables can also be supplied as pre-terminated fibre optic trunks. Photographs are not to scale and do not represent detailed images of the respective products. Available on request with Multimode OM4 fibres.

Accessories

- STAR STRIP stripping tool refer to page 910
- SMART STRIP stripping tool refer to page 911