

BIOFLEX-500®-JZ-HF-C Biofuel-resistant, abrasion-resistant, recyclable, environmentally friendly, drag-chain cable, bio-oil resistant ¹⁾, meter marking



Technical data

- Bio-oil resistant, abrasion resistant special high flexible control cable adapted to DIN VDE 0285-525-1 / DIN EN 50525-1
- **Temperature range**
flexing -20°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage** U₀/U 300/500 V
- **Test voltage** 3000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 15x cable Ø
fixed installation 4x cable Ø
- **Coupling resistance**
max. 250 Ohm/km
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Bare copper, extra fine wire conductors, bunch stranded to DIN VDE 0295 cl.6, BS 6360 cl.6 and IEC 60228 cl.6
- Core insulation of special polymer with improved sliding ability
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal selected lay-length
- Wrapping with fleece
- Special inner sheath
- Copper braided screening approx. 85% coverage
- Wrapping with fleece guarantees a good dismantling
- Outer sheath of special polymer compound
- Sheath colour dark green
- with meter marking

Properties

- **Resistant to**
Bio-fuel (diesel and petrol), highly resistant to biologically decomposable oils, Oxygene, Ozone, Hydrolysis and Microbes
- Low adhesion

Note

- G = with green-yellow conductor
x = without green-yellow conductor (OZ)
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- Unscreened analogue type:
BIOFLEX-500®-JZ-HF

Application

HELUKABEL® BIOFLEX-500®-JZ-HF-C is an extremely robust and high flexible control cable with high abrasion and tear resistant properties. Due to its high resistance to Bio-fuel, Bio-oil and coolant emulsions. It is especially suited for use in the machine, tool making and plant industries as well as in the steel industry for difficult and problem areas. Suitable in combination with cable trays in dry, moist and wet rooms and outdoor installation. The high flexibility of this cable type makes it quick and easy to install. Suitable for outdoor lying. These screened cables are particularly suitable for the interference-free transmission in instrumentation and control engineering applications (electromagnetic compatibility). For the critical applications we advise for consultation. For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc.) we recommend for our especially developed enquiry sheet for energy guiding systems. Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see lead text.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
25826	2 x 0,5	7,5	47,0	90,0	20	25849	5 G 1	11,8	99,0	188,0	18
25827	3 G 0,5	7,8	52,0	104,0	20	25850	7 G 1	12,7	125,0	235,0	18
25828	4 G 0,5	8,2	55,0	123,0	20	25851	10 G 1	14,6	178,0	340,0	18
25829	5 G 0,5	9,9	65,0	131,0	20	25852	12 G 1	15,5	186,0	358,0	18
25830	7 G 0,5	10,0	84,0	172,0	20	25853	14 G 1	16,7	250,0	415,0	18
25831	10 G 0,5	11,3	115,0	230,0	20	25854	18 G 1	18,0	280,0	500,0	18
25832	12 G 0,5	12,5	117,0	250,0	20	25855	25 G 1	21,0	378,0	678,0	18
25833	14 G 0,5	13,2	148,0	280,0	20	25856	2 x 1,5	10,5	79,0	141,0	16
25834	18 G 0,5	14,5	157,0	321,0	20	25857	3 G 1,5	10,8	94,0	164,0	16
25835	25 G 0,5	16,8	227,0	445,0	20	25858	4 G 1,5	11,5	113,0	220,0	16
25836	2 x 0,75	8,3	53,0	106,0	19	25859	5 G 1,5	12,5	129,0	233,0	16
25837	3 G 0,75	8,5	62,0	120,0	19	25860	7 G 1,5	13,2	170,0	323,0	16
25838	4 G 0,75	9,5	77,0	150,0	19	25861	8 G 1,5	14,4	226,0	369,0	16
25839	5 G 0,75	10,8	86,0	158,0	19	25862	10 G 1,5	14,9	258,0	461,0	16
25840	7 G 0,75	11,5	107,0	205,0	19	25863	12 G 1,5	16,2	280,0	481,0	16
25841	10 G 0,75	13,1	148,0	290,0	19	25864	14 G 1,5	18,1	340,0	561,0	16
25842	12 G 0,75	14,0	156,0	304,0	19	25865	18 G 1,5	20,3	395,0	672,0	16
25843	14 G 0,75	15,3	214,0	380,0	19	25866	21 G 1,5	21,7	461,0	780,0	16
25844	18 G 0,75	17,3	235,0	418,0	19	25867	25 G 1,5	23,1	533,0	927,0	16
25845	25 G 0,75	18,7	313,0	578,0	19	25868	2 x 2,5	11,8	96,0	185,0	14
25846	2 x 1	10,0	60,0	116,0	18	25869	3 G 2,5	13,0	150,0	278,0	14
25847	3 G 1	10,2	70,0	135,0	18	25870	4 G 2,5	14,0	174,0	370,0	14
25848	4 G 1	11,0	86,0	178,0	18	25871	5 G 2,5	15,1	200,0	412,0	14

Continuation ▶

BIOFLEX-500®-JZ-HF-C Biofuel-resistant, abrasion-resistant, recyclable, environmentally friendly, drag-chain cable, bio-oil resistant ¹⁾, meter marking



Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
25872	7 G 2,5	16,2	240,0	470,0	14
25873	12 G 2,5	21,0	410,0	738,0	14
25874	14 G 2,5	23,4	480,0	870,0	14
25875	18 G 2,5	25,7	620,0	1100,0	14
25876	25 G 2,5	31,0	821,0	1512,0	14
25877	2 x 4	13,4	135,0	235,0	12
25878	3 G 4	15,8	178,0	350,0	12
25879	4 G 4	17,3	222,0	460,0	12
25880	5 G 4	19,0	328,0	550,0	12

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
25881	3 G 6	19,5	250,0	525,0	10
25882	4 G 6	21,0	305,0	700,0	10
25883	5 G 6	23,0	441,0	800,0	10
25884	3 G 10	18,8	370,0	855,0	8
25885	4 G 10	25,0	485,0	1140,0	8
25886	5 G 10	26,4	610,0	1310,0	8
25887	4 G 16	28,0	840,0	1391,0	6

Dimensions and specifications may be changed without prior notice. (RC03)