

SUPERTRONIC® -C-PURö

cable for drag chains, halogen-free, meter marking, EMC-preferred type



HELUKABEL SUPERTRONIC-C-PURö 4x0,25 QMM / 49666 500 V 001042077



Technical data

- Special PUR drag chain cables, screened, adapted to DIN VDE 0285-525-1 / DIN EN 50525-2-51
- **Temperature range**
flexing -30°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage**
0,14 mm² 350 V
from 0,25 mm² 500 V
- **Test voltage**
0,14 mm² 800 V
from 0,25 mm² 1200 V
- **Capacitance**
core/core < 80 nF/km
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Coupling resistance**
max. 250 Ohm/km
- **Radiation resistance**
up to 100x10⁶ CJ/kg (up to 100 Mrad)

Cable structure

- Bare copper conductors, extra fine wire, acc. to DIN VDE 0295 cl.6, IEC 60228 cl.6
- Core insulation of PP
- Core identification to DIN 47100
- Cores stranded in layers with optimal lay length
- Wrapping
- Tinned copper braided screen, approx. 85% coverage
- Fleece wrapping
- Outer sheath of special **full-polyurethane** TMPU to DIN VDE 0207-363-10-2 / DIN EN 50363-10-2
- Sheath colour: grey (RAL 7001), surface mat
- With meter marking

Properties

- **Features**
High flexibility at low temperature, high abrasion resistance, break and cut-resistant, tear resistant
- **Resistant to**
UV-radiation, Oxygen, Ozone, Hydrolyse, Oil
- **Conditional resistant to**
Microbes, Hydraulic liquidity, Alkalis, Lye
- The PUR outer sheath is extremely robust with high tear, abrasion and oil-resistance
- Adhesion-low
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Note

- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Application

Used for installation in dry, moist and wet environments as well as for outdoors, for free movement without forced motion and for flexible routing without forced motion, for proven use as drag-chain cables. Suitable as a highly flexible control cable for fast hoisting and bending stresses in machinery and tooling construction, in robotics engineering and for continuously moving machinery parts. The long working life of this cable makes it both efficient and economic. The copper braided screening offers effective protection from both internal and external interference. For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc.) we recommend for our especially developed enquiry sheet for energy guiding systems. Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see chapter "Technical Informations".

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
49653	2 x 0,14	4,2	11,0	32,0	26	49670	12 x 0,25	8,1	59,0	124,0	24
49654	3 x 0,14	4,4	14,0	35,0	26	49671	14 x 0,25	8,4	64,0	135,0	24
49655	4 x 0,14	4,7	16,0	40,0	26	49672	18 x 0,25	9,4	78,0	160,0	24
49656	5 x 0,14	5,2	18,0	45,0	26	49673	24 x 0,25	10,9	90,0	202,0	24
49657	7 x 0,14	5,9	28,0	66,0	26	49674	25 x 0,25	11,4	101,0	211,0	24
49658	10 x 0,14	6,9	39,0	86,0	26	49675	2 x 0,34	5,0	18,0	45,0	22
49659	12 x 0,14	7,1	42,0	94,0	26	49676	3 x 0,34	5,2	29,0	60,0	22
49660	14 x 0,14	7,4	45,0	102,0	26	49677	4 x 0,34	5,6	36,0	76,0	22
49661	18 x 0,14	8,2	54,0	118,0	26	49678	5 x 0,34	6,2	39,0	82,0	22
49662	24 x 0,14	9,5	66,0	149,0	26	49679	7 x 0,34	7,1	53,0	110,0	22
49663	25 x 0,14	9,9	68,0	156,0	26	49680	10 x 0,34	8,3	67,0	148,0	22
49664	2 x 0,25	4,6	14,9	38,0	24	49681	12 x 0,34	8,5	76,0	166,0	22
49665	3 x 0,25	5,0	19,0	44,0	24	49682	14 x 0,34	8,9	86,0	185,0	22
49666	4 x 0,25	5,3	21,3	51,0	24	49683	18 x 0,34	9,9	100,0	216,0	22
49667	5 x 0,25	5,7	31,0	68,0	24	49684	24 x 0,34	11,5	147,0	300,0	22
49668	7 x 0,25	6,8	40,0	82,0	24	49685	25 x 0,34	12,0	155,0	313,0	22
49669	10 x 0,25	7,9	54,0	110,0	24						

Dimensions and specifications may be changed without prior notice. (RC03)