

SUPERTRONIC® -PURö

special cable for drag chains, meter marking



HELUKABEL SUPERTRONIC-PURö 4x0,25 QMM / 49596 350 V 001042052

CE

Technical data

- Special PUR drag chain cables adapted to DIN VDE 0285-525-2-51 / DIN EN 50525-2-51
- Very high flexible due to special construction
- **Temperature range**
flexing -5°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage**
350 V
- **Test voltage**
1500 V
- **Breakdown voltage**
min. 3000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 5x cable Ø
fixed installation 3x cable Ø
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Bare copper conductor, extra fine wire, acc. to DIN VDE 0295 cl.6, col. 4 and 5 IEC 60228 cl.6
- **Oil resistant** PVC core insulation TI2, adapted to DIN VDE 0207-363-3 / DIN EN 50363-3, for better sliding abilities
- Core identification to DIN 47100, coloured
- Cores stranded in layers with optimal lay length
- Core wrapping with textile tape
- Outer sheath of special **full-polyurethane** TMPU to DIN VDE 0207-363-10-2 / DIN EN 50363-10-2
- Sheath colour: grey (RAL 7001), surface mat
- With meter marking

Properties

- **Features**
High flexibility at low temperature, high abrasion resistance, break and cut-resistant, tear resistant
- **Resistant to**
UV-radiation, Oxygen, Ozone, Hydrolyse, Oil.
- **Conditional resistant to**
Microbes, Hydraulic liquidity, Alkalis, Lye.
- The PUR outer sheath is extremely robust with high tear, abrasion and oil-resistance.
- Adhesion-low
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Note

- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Application

Perfect for use with cable trays. This highly flexible PUR control cable is ideal for use wherever frequent high flexing motion is required, e. g. in robotics or all moving parts. The long working life of this cable makes it both efficient and economic. For applications which go beyond standard solutions (for example for composting appliances or high shelf conveyors with extremely high processing speeds etc.) we recommend for our especially developed enquiry sheet for energy guiding systems. Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see chapter "Technical Informations".

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
49583	2 x 0,14	3,5	2,8	22,0	26
49584	3 x 0,14	3,7	4,1	24,0	26
49585	4 x 0,14	3,9	5,6	29,0	26
49586	5 x 0,14	4,2	7,0	33,0	26
49587	7 x 0,14	4,9	9,8	47,0	26
49588	10 x 0,14	6,2	14,0	59,0	26
49589	12 x 0,14	6,4	16,8	67,0	26
49590	14 x 0,14	6,6	19,6	74,0	26
49591	18 x 0,14	7,3	25,2	86,0	26
49592	24 x 0,14	8,5	33,6	115,0	26
49593	25 x 0,14	8,6	35,0	120,0	26
49594	2 x 0,25	4,1	5,0	27,0	24
49595	3 x 0,25	4,3	7,5	33,0	24
49596	4 x 0,25	4,8	10,0	40,0	24
49597	5 x 0,25	5,2	12,5	48,0	24
49598	7 x 0,25	6,2	17,5	60,0	24
49599	10 x 0,25	7,4	25,0	79,0	24

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
49600	12 x 0,25	7,6	30,1	91,0	24
49601	14 x 0,25	7,9	35,0	102,0	24
49602	18 x 0,25	8,9	45,0	125,0	24
49603	24 x 0,25	10,0	60,0	163,0	24
49604	25 x 0,25	10,6	62,5	170,0	24
49605	2 x 0,34	4,5	6,8	32,0	22
49606	3 x 0,34	4,9	10,2	40,0	22
49607	4 x 0,34	5,3	13,6	55,0	22
49608	5 x 0,34	5,8	17,0	60,0	22
49609	7 x 0,34	6,9	23,8	80,0	22
49610	10 x 0,34	8,4	34,0	112,0	22
49611	12 x 0,34	8,6	40,8	127,0	22
49612	14 x 0,34	9,0	47,6	142,0	22
49613	18 x 0,34	10,1	61,2	175,0	22
49614	24 x 0,34	12,0	81,5	229,0	22
49615	25 x 0,34	12,2	85,0	238,0	22

Dimensions and specifications may be changed without prior notice. (RC03)