



TOPFLEX®-EMV-3 PLUS 2YSLCY-J

for power supply connections to frequency converters, double screened, 0,6/1 kV, meter marking



Technical data

- Special motor power supply cable for frequency converters adapted to DIN VDE 0250
- **Temperature range**
flexing +5°C to +70°C
fixed installation -40°C to +70°C
- **Nominal voltage**
U₀/U 600/1000 V
- **Max. operating voltage**
A.C. and 3-phase 700/1200 V
DC operation 900/1800 V
- **Test voltage**
4000 V
- **Coupling resistance**
acc. to different cross sections
max. 250 Ohm/km
- **Minimum bending radius**
flexing for cable Ø:
up to 12 mm: 10x cable Ø
> 12 mm: 15x cable Ø
fixed installation 4x cable Ø
- **Radiation-resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper conductor, to DIN VDE 0295 cl.5, fine wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of polyethylene (PE)
- Core identification BK, BN, GY
- GN-YE conductor (divided into 3)
- 3+3-core structure
- Cores stranded in concentric layers
- 1. Screen with special aluminium film
- 2. Tinned copper braided screen, approx. 85% coverage
- Outer sheath of special PVC
- Sheath colour: transparent
- With meter marking

Note

- **)The current carrying capacity for permanent operation at ambient temperature of 30°C. For deviating ambient temperatures the conversion factors should be used and for further see the indication in DIN VDE 0298 part 4.
- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Properties

- Low mutual capacitance
- Low coupling resistance for high electromagnetic compatibility
- The minimum cross section of 0,75² meets the requirements of DIN EN 60204 part 1.
- The 3 PLUS-construction of motor power supply cables features a symmetrical 3-core design, improved in terms of EMC characteristics comparing favorably with a 4-core version. The protective conductor PE, divided into 3 is uniformly stranded in the interstices. This enables an extremely concentric structure.
- This screened motor supply cable with low mutual capacitance of the single cores because of the special PE core insulation and low screen capacitance enable a low-loss transmission of the power compared to PVC-sheathed connecting cables
- Due to the optimal screening an interference-free operation of frequency converters is obtained
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B)
- Meets EMC requirements acc. to EN 55011 and DIN VDE 0875 part 11

Application

As a supply and connecting cable for medium mechanical stresses in fixed installations and forced movements in dry, moist and wet environments, not however for outdoor applications. Used in the automotive and food industries, environmental technology, packaging industry, chemical industry.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Coupling resistance		Power ratings **)	Cop. weight	Weight	AWG-No.
			at 1 MHz	at 30 MHz	with 3 loaded cores	kg / km	app. kg / km	
			Ohm/km	Ohm/km	in Amperes			
22368	3 x 1,5 + 3 G 0,25	9,2			18	86,0	140,0	16
22369	3 x 2,5 + 3 G 0,5	10,8	18	210	26	144,0	220,0	14
22370	3 x 4 + 3 G 0,75	12,3	11	210	34	224,0	323,0	12
22371	3 x 6 + 3 G 1,0	14,0	6	150	44	298,0	420,0	10
22372	3 x 10 + 3 G 1,5	17,6	7	180	61	491,0	615,0	8
22373	3 x 16 + 3 G 2,5	21,2	9	190	82	723,0	819,0	6
22374	3 x 25 + 3 G 4,0	24,5	4	95	108	1138,0	1325,0	4
22375	3 x 35 + 3 G 6,0	26,9	3	85	135	1535,0	1718,0	2
22376	3 x 50 + 3 G 10,0	32,5	2	40	168	2208,0	2399,0	1
22377	3 x 70 + 3 G 10,0	35,5	2	45	207	2871,0	3056,0	2/0
22378	3 x 95 + 3 G 16,0	40,1	1	50	250	3953,0	4162,0	3/0
22379	3 x 120 + 3 G 16,0	44,4			292	4836,0	5074,0	4/0
22380	3 x 150 + 3 G 25,0	49,3			335	5412,0	6128,0	300 kcmil
22381	3 x 185 + 3 G 35,0	55,1			382	6969,0	7189,0	350 kcmil
22382	3 x 240 + 3 G 42,5	60,0			453	8540,0	9540,0	500 kcmil

Dimensions and specifications may be changed without prior notice. (RD01)