



TOPFLEX®-EMV-UV-2XSLCYK-J

for power supply connections to frequency converters, double screened, higher current carrying capacity, 0,6/1 kV, meter marking



Technical data

- Special motor power supply cable for frequency converters adapted to DIN VDE 0250
- **Temperature range**
flexing -5°C to +90°C
fixed installation -40°C to +90°C
- Permissible **operating temperature** at conductor +90°C
- **Nominal voltage**
U₀/U 600/1000 V
- Max. **operating voltage**
A.C. and 3-phase 700/1200 V
DC operation 900/1800 V
- **Test voltage**
4000 V
- **Coupling resistance**
acc. to different cross sections
max. 250 Ohm/km
- **Minimum bending radius**
flexing for cable Ø:
up to 12 mm: 10x cable Ø
> 12 mm: 15x cable Ø
fixed installation 4x cable Ø
- **Radiation-resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper conductor, to DIN VDE 0295 cl.5, fine wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of cross-linked polyethylene (XLPE)
- Core identification BN, BK, GY
- GN-YE conductor
- Cores stranded in concentric layers
- 1. Screen with special aluminium film
- 2. Tinned copper braided screen, approx. 85% coverage
- Outer sheath of special PVC
- Sheath colour: black (RAL 9005)
- With meter marking

Note

- **) The current carrying capacity for permanent operation at ambient temperature of 30°C. For deviating ambient temperatures the conversion factors should be used and for further see the indication in DIN VDE 0298 part 4.
- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Properties

- Low mutual capacitance
- Low coupling resistance for high electromagnetic compatibility
- UV-resistant
- Outdoor application
- This screened motor supply cable with low mutual capacitance of the single cores because of the special XLPE core insulation and low screen capacitance enable a low-loss transmission of the power compared to PVC-sheathed connecting cables
- Due to the optimal screening an interference-free operation of frequency converters is obtained
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Tests

- self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B)
- Meets EMC requirements acc. to EN 55011 and DIN VDE 0875 part 11

Application

As a supply and connecting cable for medium mechanical stresses in fixed installations and forced movements in dry, moist and wet environments and for outdoor applications, possible for installation in underground at 4G16 mm². Respecting the permissible operating temperature at the conductor of +90 °C permits a higher current carrying capacity than PE insulated power distribution cables. Used in the automotive and food industries, environmental technology, packaging industry, chemical industry.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Continuation ►

TOPFLEX®-EMV-UV-2XSLCYK-J

for power supply connections to frequency converters, double screened, higher current carrying capacity, 0,6/1 kV, meter marking

Part no.	No.cores x cross-sec. mm ²	Outer Ø app. mm	Mutual capacitance		Coupling resistance		Power ratings **) with 3 loaded cores in Amperes	Cop. weight kg / km	Weight app. kg / km	AWG-No.
			Core / Core app. nF / km	Core / Screen app. nF / km	at 1 MHz Ohm/km	at 30 MHz Ohm/km				
24489	4 G 1,5	10,1	70	110			23	95,0	230,0	16
24490	4 G 2,5	11,2	80	130	18	210	32	150,0	300,0	14
24491	4 G 4	12,8	90	150	11	210	42	235,0	485,0	12
24492	4 G 6	14,9	90	150	6	150	54	320,0	630,0	10
24493	4 G 10	17,7	120	200	7	180	75	533,0	860,0	8
24494	4 G 16	20,9	120	210	9	190	100	789,0	1290,0	6
24495	4 G 25	25,3	140	230	4	95	127	1236,0	1860,0	4
24496	4 G 35	28,0	150	260	3	85	158	1662,0	2610,0	2
24497	4 G 50	32,3	190	320	2	40	192	2345,0	2950,0	1
24498	4 G 70	37,6	190	320	2	45	246	3196,0	3950,0	2/0
24499	4 G 95	41,6	250	410	1	50	298	4316,0	5300,0	3/0
24500	4 G 120	44,8					346	5435,0	6600,0	4/0
24506	4 G 150	52,3					399	6394,0	7040,0	300 kcmil
24507	4 G 185	58,7					456	7639,0	8380,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RD01)