


# CABLE SPECIFICATION

Sectional view:



Coding content:

 ALTEK KABEL 4PR 18AWG TWISTED SCREENED AUDIO & INSTRUMENTATION CABLE + Meter

<b>Model</b>	8760 4P×18AWG	
<b>Conductor</b>	16/0.24 Tinned copper stranding	
<b>Maximum conductor resistance <math>\Omega</math> / KM (20 °C)</b>	23.9	
<b>ID</b>	2.1±0.1mm	
<b>Core color</b>	Black, transparent; Black, red; Black, white; Black, blue	
<b>Insulation Materials</b>	HDPE	
<b>Twisted pair</b>	Black, transparent; Black, red; Black, white; Black, blue	
<b>Each pair wrapping</b>	Aluminum foil (conductive layer facing outward)	
<b>Synchronization completed</b>	<b>Stranding</b>	Four pairs of twisted
	<b>Ground wire</b>	15/0.18 Tinned copper stranding
<b>Wrapping</b>	Mylar	
<b>Jacket</b>	Grey (PVC-80P)	
<b>OD</b>	11.8±0.3mm	
<b>Sheath thickness</b>	1.4mm	
<b>Rated voltage</b>	300/300V	
<b>Processing methods and scope</b>	Cabling project, without processing	

<b>Draw</b>	<b>Audit</b>	<b>Approved</b>

Customer Confirm:

**SHENZHEN HAILUTONG WIRE&CABLE CO.,LTD**