

Publish Date: 05.02.2021 | Rev no: 1

### DUCPHAT® SC/SC Duplex OS2 Patch Cords - UPC

DUC PHAT manufactures a wide range of factory terminated and tested fiber optic patch cords. Available in various fiber types and fiber/cable constructions and connector options, our factory-based assembly and machine connector polishing systems ensure excellence in performance, inter-connectability and durability. All patch cords are 100% tested using standards-based testing procedures.

DUCPHAT® single patch cords are high-performance, high-quality patch cords used for LAN's, Datacenters, Telecom & FTTx networks, and also high speed metropolitan and WAN networks. The DUCPHAT® patch cords are manufactured using PVC cable which conforms to IEC & TIA standards. The patch cords are terminated with the highest quality connectors, giving them optimum optical performance and reliable repeatability.

#### Features

- \* Connector types available LC/SC/ST/FC/MTRJ/MTP/MPO
- \* 100% end face inspected & compliance with GR-326-CORE
- \* High-quality, machine polished connectors for consistent low loss performance
- \* Short buffer style connector boots for ease of fiber management in high density applications

#### Applications



- \* High speed LAN, MAN, WAN networks and Data Centers
- \* CATV / VIDEO / WDM / DWDM / FTTx / ATM, SONET & WDM
- \* FTTH, FTTx and Passive Optical Networks PON
- \* High speed multi channel video, data and voice services in metropolitan and access networks

#### Technical Properties

- \* Connector types: SC - SC
- \* Jacket: PVC
- \* Insertion Loss: Singlemode:  $\leq 0.15\text{dB}$  typical /  $\leq 0.30\text{dB}$  maximum
- \* Return Loss Singlemode: APC  $\leq 35\text{dB}$  / UPC  $\leq 35\text{dB}$  / PC  $\leq 35\text{dB}$
- \* Polish Type: UPC
- \* Operating Temperature: -40 to +85°C

#### Standards Compliance

- \* Compliant to TIA 604-5 and IEC 61754-7
- \* Standards ISO/IEC 11801 / Cenelec EN 50173-1 / TIA-568 C.0
- \* Data Center Cenelec EN 50173-5 / ISO/IEC 24764/ TIA-942
- \* Ethernet IEEE 802.3; 10/40/100GbE
- \* RoHS-6 Compliant



#### Ordering Information

| Item               | Item                         |
|--------------------|------------------------------|
| <b>Jumper Cord</b> | <b>DP-JC-AB/AB-C-D-E-F-G</b> |

| A    | Connector type |
|------|----------------|
| SC   | SC Connector   |
| FC   | FC Connector   |
| ST   | ST Connector   |
| LC   | LC Connector   |
| MTRJ | MTRJ Connector |

| B     | Polishing |
|-------|-----------|
| Blank | PC type   |
| AC    | APC type  |

| C  | Fiber type              |
|----|-------------------------|
| SM | Single mode (SM), G.652 |
| S5 | Single mode (SM), G.655 |
| S7 | Single mode (SM), G.657 |
| M1 | Multi mode (OM1)        |
| M2 | Multi mode (OM2)        |
| M3 | Multi mode (OM3)        |
| M4 | Multi mode (OM4)        |

| D  | Cable Diameter |
|----|----------------|
| 09 | 0.9mm          |
| 20 | 2.0mm          |
| 24 | 2.4mm          |
| 30 | 3.0mm          |

| E  | Connector type  |
|----|-----------------|
| SP | Simplex Cord    |
| DP | Duplex Zip Cord |

| F | Cable Jacket |
|---|--------------|
| V | PVC          |
| Z | LSZH         |

| G   | Length (M) |
|-----|------------|
| 005 | 0.5m       |
| 10  | 1m         |
| 100 | 10m        |

\* Other lengths available on request \*

**DUC PHAT TELECOM EQUIPMENT CO.,LTD**

**No. 10 Alley 163/30/2 Tu Dinh Street, Long Bien Ward, Long Bien District, Hanoi City, Vietnam**

**P: +84 985727232 E-mail: kd.ducphat@gmail.com W: www.ulcab.com.vn**