
## **CABLE SPECIFICATION**

## Sectional view:



Ground wire: 11/0.18 tinned copper stranded Conductor: 7/0.24 tinned copper stranded Core wire: black. red; white. green (HDPE)

Wrapping:Aluminum foil (conductive layer facing outward)

Braiding:128/0.10 Tinned copper

Jacket: black (PVC-70P)

Coding content:



ALTEK KABEL RS485 2 PAIR 22AWG SCREENED LOW CAPACITANCE COMPUTER CABLE + Meter

	Model		RS485 2P×22AWG+B				
	Conducto	or	7/0.24 Tinned copper stranding				
	Maximum con resistance Ω / K		60.7				
	ID		2.2±0.1mm				
	Core cole	or	Black, red; white, green				
	Insulation Ma	terials	HDPE				
	Twisted pair		Black, red; white, green				
	Each pair wra	apping	Aluminum foil (conductive layer facing outward)				
	Synchronization	Stranding	Two-Pairs stranding				
	completed	Ground wire	11/0.18 Tinned copper stranding				
	braiding	9	128/0.10 Tinned copper				
	Jacket OD Sheath thickness		Black(PVC-70P)				
			9.5±0.2mm				
			1.0mm				
	Rated voltage		300/300V				
	Processing methods and scope		Cabling project, without processing				
	SHENZHEN HAILUTONG WIRE&CABLE COLTD						

	Draw	Audit	Approved	scope	processing
Customer Confirm:	SHENZHEN HAILUTOI		WIRE&CABLE CO.,LTD		