

# Bảng thông số sản phẩm

Thông số kỹ thuật



## APC Easy UPS On-Line SRV 1000VA 230V with Extended Runtime Battery Pack

SRV1KIL

### Overview

**Presentation** High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

**Lead time** Usually in Stock

### Main

<b>Rated power in W</b>	800 W
<b>Rated power in VA</b>	1000 VA
<b>Nb of power socket outlets</b>	3 IEC 60320 C13
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Plug standard</b>	IEC 60320 C14
<b>Cable length</b>	1.50 m
<b>Number of cables</b>	1

### General

<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Provided equipment</b>	Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord 1 x DC cable User manual USB cable

### Physical

<b>Mounting mode</b>	Not rack-mountable
<b>Height</b>	23.8 cm
<b>Width</b>	29 cm
<b>Depth</b>	40 cm
<b>Net weight</b>	24 kg
<b>Colour</b>	Black

## Input

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	CE EAC TISI
Standards	EN/IEC 62040-1 EN/IEC 62040-2

## Environmental

Acoustic level	50 dBA
Heat dissipation	372 Btu/h
Operating altitude	0...3000 m
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	Non-condensing 0...95 %

## Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	36 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4.5 h

Battery life	3...5 year(s)
Battery charger power	175 W rated
Battery option	SRV36BP-9A 1 1032 VAh SRV36BP-9A 2 1548 VAh SRV36BP-9A 3 2064 VAh SRV36BP-9A 4 2580 VAh SRV36BP-9A

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console
Free slots	1

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Package 1 Weight	26.7 kg
Package 1 Height	35.5 cm
Package 1 width	47 cm
Package 1 Length	52.5 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Under investigation

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------