

# AWM 1061 STYLE

Single conductor using extruded non-integral jacket.

Standard UL Subject 758 / UL Standard 1581



## 제품용도(Applications)

전기 전자 기기의 내부 배선용.  
높은 기계적 강도 요구 배선용.

Internal Wiring in Electric Bookkeeping, Accounting, Time-recording, Machines, or Electronics Equipment if within a chassis or protected from mechanical injury.

## 제품특성(Characteristic)

- 정격(Rating Temp.& Volt) : UL 80°C 300V
- 난연성(Flammability) : VW-1, FT1 Pass
- 생산범위(Product Range) : 30AWG~14AWG

## 제품 구조(Construction)



사이즈 AWG Size	도체 Conductors		절연체 Insulation		최대도체저항 Conductor Max Resistance Ω/km	최소절연저항 Insulation Min. Resistance MΩ/km	내전압 Dielectric Withstanding Voltage AC V/min	허용전류 Allowable Current A
	구성 Number&dia of conductors pcs/■	외경 Nor. overall Diameter ■	평균두께 Nominal Thickness ■	외경 Nor. overall Diameter ■				
30	7/0.10	0.30	0.25	0.80	376.96	15	3,000	2.0
28	7/0.127	0.38	0.25	0.90	237.38			2.6
26	7/0.16	0.48	0.25	1.00	148.94			3.4
24	11/0.16	0.61	0.25	1.10	93.25			4.6
22	17/0.16	0.76	0.25	1.30	55.00			6.1
20	21/0.18	0.95	0.25	1.50	34.60			8.4
18	34/0.18	1.21	0.25	1.80	21.80			11.3
16	26/0.254	1.55	0.25	2.10	13.70			15.2