

AWM 1332 STYLE

Single conductor with Covering



Standard UL Subject 758



제품용도(Applications)

가전 제품의 내부 배선.
Internal Wiring of Appliances.

제품특성(Characteristic)

- 정격(Rating Temp.& Volt) : UL 200°C 300Vac.
- 난연성(Flammability) : VW-1, FT1 Pass
- 생산범위(Product Range) : 30AWG - 10AWG
- Halogen Free (할로겐프리 친환경 케이블)

제품 구조(Construction)



사이즈 AWG Size	도체 Conductors		절연체 Insulation		최대도체저항 Conductor Max Resistance Ω/㎞	최소절연저항 Insulation Min. Resistance ㎞/㎞	내전압 Dielectric Withstanding Voltage AC V/min
	구성 Number&dia of conductors pcs/㎞	외경 Nor. overall Diameter ㎞	평균두께 Nominal Thickness ㎞	외경 Nor. overall Diameter ㎞			
30	7/0.10	0.30	0.33	0.95	376.96	15	2,000
28	7/0.127	0.38	0.33	1.05	237.38		
26	7/0.16	0.48	0.33	1.15	148.94		
24	11/0.16	0.61	0.33	1.30	93.25		
22	17/0.16	0.76	0.33	1.40	55.00		
20	21/0.18	0.95	0.33	1.60	34.60		
18	41/0.16	1.21	0.33	1.90	21.80		
16	26/0.254	1.55	0.33	2.20	13.70		
14	41/0.254	1.88	0.33	2.55	8.96		
12	65/0.254	2.36	0.33	3.00	5.64		
10	66/0.320	3.00	0.33	3.65	3.55		