



✓ installation ✓ mobile ✓ RoHS ✓ REACH ✓ CE

## L-RP 2 x 1,50 qmm

PVC

Order-No. 650215000

### Application / Description

---

Very flexible but also durable speaker-cable for mobile using or fixed installation on stages and in studios as well as for HiFi- and PA-systems.

### Variant data

---

O.D.	approx. 6,20 mm
weight	65,0 kg/km
Cu-weight	28,8 kg/km

### Construction / data

---

Cross section	1,50 qmm
---------------	----------

### Construction / audio

---

Conductor	finest, bare stranded copper wire
Core insulation	PVC

### Construction

---

Outer jacket	PVC
Outer jacket colour	black-matt, soft
Dimension	2 x 1,50 qmm

### Technical characteristics

---

Temperature range	static: -20 °C to +70 °C dynamic: -5 °C to +70 °C
Bending radius	> 10 x O.D.
Operating voltage	500 V
Testing voltage	2.500 V



## Packaging

---

### Rings, Reels

Lower and upper lengths according to availability. Special packaging on request.

*Technische Änderungen und Irrtümer vorbehalten. Die Eignung für einen konkreten Verwendungszweck muss vom Kunden geprüft werden.*

*Technical changes and errors reserved. The suitability for a specific purpose must be checked by the customer.*

© kabeltronik® Arthur Volland GmbH

Mühlweg 6, 85095 Denkendorf

Tel.: 08466 - 9404-0

E-Mail: [info@kabeltronik.de](mailto:info@kabeltronik.de)

 **kabeltronik**®