



✓ installation ✓ mobile ✓ RoHS ✓ REACH ✓ CE

L-RP 2 x 4,00 qmm

PVC

Order-No. 650240000

Application / Description

Very flexible but also durable speaker-cable for mobile using or fixed installation on stages and in studios as well as for HiFi- and PA-systems.

Variant data

O.D.	approx. 10,00 mm
weight	139,0 kg/km
Cu-weight	76,8 kg/km

Construction / data

Cross section	4,00 qmm
---------------	----------

Construction / audio

Conductor	finest, bare stranded copper wire
Structure of conductor	224 x 0,15 mm
number of cores	2
Core insulation	PVC

Construction

Outer jacket	PVC
Outer jacket colour	black-matt, soft
Dimension	2 x 4,00 qmm

Technical characteristics

Temperature range	static: -20 °C to +70 °C dynamic: -5 °C to +70 °C
Bending radius	> 10 x O.D.



Operating voltage	500 V
Testing voltage	2.500 V
Conductor resistance	max. 4,8 Ohm/km

Packaging

Rings, Reels

Lower and upper lengths according to availability. Special packaging on request.

*Technische Änderungen und Irrtümer vorbehalten. Die Eignung für einen konkreten Verwendungszweck muss vom Kunden geprüft werden.
Technical changes and errors reserved. The suitability for a specific purpose must be checked by the customer.*

© kabeltronik® Arthur Volland GmbH
Mühlweg 6, 85095 Denkendorf
Tel.: 08466 - 9404-0
E-Mail: info@kabeltronik.de

 **kabeltronik**®