

COMPANY PROFILE

公司简介

深圳市宏观盛科技有限公司

SHENZHEN HONGGUANSHENG SCIENCE AND TECHNOLOGY LTD.

深圳市宏观盛科技有限公司成立于2010年，公司坐落于深圳龙岗，注册资金500万元，是国内一家集研发、生产、加工销售为一体的综合型电线电缆生产企业。

产品广泛用于电子电器、照明灯具、电子设备、机械电气、电热制品及汽车工业。

SHENZHEN HONGGUANSHENG SCIENCE AND TECHNOLOGY LTD. WAS FOUNDED IN 2010 AND LOCATED IN SHENZHEN, WITH A REGISTERED CAPITAL OF 5 MILLION YUAN. WE ARE A COMPREHENSIVE STRENGTH COMPANY THAT INTEGRATES TECHNOLOGICAL R&D, MANUFACTURING, PROCESSING AND SALES. OUR PRODUCTS ARE WIDELY USED IN ELECTRONIC APPLIANCES, LIGHTING LAMPS, ELECTRONIC EQUIPMENT, MECHANICAL AND ELECTRICAL, ELECTRIC HEATING PRODUCTS AND AUTOMOTIVE INDUSTRY.

公司主营产品为:1007、1015、1571、1061、1672、2651、2725、20276、2835、1617、1095、1569、2517、2468、2464、1533、1185、2547等PVC电子线，RVB红黑线、RVVB电源线、RV、BVR、BVV电线、RVV电缆线、RVVP屏蔽线、耐油耐温电线电缆、对绞电缆、硅胶线 铁氟龙 编织高温线云母高温线等系列产品。

1007,1015,1571,1061,1672,2651,2725,20276,2835,1617,1569,2517,2468,2464,1533,1185,2547ETC. PVC ELECTRONIC WIRE, RVB RED AND BLACK WIRE, RVVB POWER CORD, RV,BVR,BVV WIRE, RVV CABLE, RVVP SHIELDED WIRE, OIL AND TEMPERATURE RESISTANT WIRE AND CABLE, PAIR OF TWISTED CABLE, SILICONE WIRE, TEFLON, WOVEN HIGH TEMPERATURE WIRE MICA HIGH TEMPERATURE WIRE AND OTHER PRODUCTS.

创新科技 专业专注

INNOVATION, PROFESSIONAL & FOCUS

产品严格按照ISO9001质量管理体系标准生产，每道环节有专门的质检人员把关，拥有多台质检设备。产品选用NP级原料，不含邻苯二甲酸，环保无毒，环保级别更是在ROHS之上，我们拥有多项产品专利，汇聚众多高素质管理人员和专业技术人员，致力于为消费者打造安全放心的品质线缆。

PRODUCTS IN STRICT ACCORDANCE WITH THE ISO9001 QUALITY MANAGEMENT SYSTEM STANDARD PRODUCTION. EACH LINK HAS A SPECIAL QUALITY INSPECTION PERSONNEL CHECK, WITH A NUMBER OF QUALITY INSPECTION EQUIPMENT. NP GRADE RAW MATERIALS ARE SELECTED FOR THE PRODUCT, PHTHALATE FREE, ENVIRONMENTAL AND NON-TOXIC, ENVIRONMENTAL PROTECTION LEVEL IS ABOVE ROHS. WE HAVE A NUMBER OF PRODUCT PATENTS, BRING TOGETHER A LARGE NUMBER OF HIGH-QUALITY MANAGEMENT TEAMS AND PROFESSIONAL TECHNICAL PERSONNEL, COMMITTED TO CREATING SAFE AND RELIABLE QUALITY CABLES FOR CONSUMERS.

公司资质 / CERTIFICATE

UL认证

CE认证

ISO9001



专利证书/PATENT



产品参数 PARAMETER

产品名称：	2464屏蔽线
Product Name	2464 Shielded wire
额定电压：	300V
Rated Voltage	
额定耐温：	80℃
Temperature resistance	
导体材质：	环保镀锡铜丝
Conduct Material	Tinned copper wires
绝缘材质：	PVC
Insulation Material	
产品认证：	UL
Product Certification	
环保标准：	RoHS、NP
Environmental Standards	



芯线颜色 COLOR

2C	3C	4C	5C	6C	7C	8C	9C	10C
红/黑	红/黑/黄	红 黑 黄 绿 红 黑 白 绿	红 黑 黄 白 绿 红 黑 黄 蓝 绿	红 黑 黄 白 绿 蓝	红 黑 蓝 黄 白 绿 棕	红/黑/黄/白/绿 蓝/橙/棕	红/黑/黄/白/绿 蓝/橙/棕/灰	红/黑/黄/白/绿 蓝/橙/棕/灰/紫
Red/Black	Red/Black/Yellow	Red/Black Yellow/Green Red/Black White/Green	Red/Black/White/ Yellow/Green Red/Black/Blue Yellow/Green	Red/Black Yellow/White Green/Blue	Red/Black/Blue/ Yellow/White Green/Brown	Red/Black Yellow/White Green/Blue Orange/Brown	Red/Black Yellow/White Green/Blue Orange/Brown/ Grey	Red/Black Yellow/White Green/Blue Orange/Brown/ Grey/Purple

产品特点 PRODUCT FEATURES

- ◆适用于广播、视听器、仪器、电脑、EIA RS232国际电工规范等
- ◆长期允许工作温度应不超过70℃
- ◆（镀锡）铜丝屏蔽编织，覆盖率达85%

◆ APPLICABLE TO BROADCASTING, AUDIO-VISUAL, INSTRUMENTS, COMPUTERS, EIA RS232 INTERNATIONAL ELECTROTECHNICAL CODE, ETC.
◆ THE LONG-TERM ALLOWABLE WORKING TEMPERATURE SHALL NOT EXCEED 70 ℃.
◆ (TINNED) COPPER WIRE SHIELD BRAID WITH 85% COVERAGE

2464屏蔽系列聚氯乙烯绝缘电线

2464 SHIELDED SERIES PVC INSULATED WIRE

产品规格 PRODUCT SPECIFICATION	外径/OD OUTSIDE DIAMETER	导体结构 CONDUCTOR STRUCTURE	屏蔽结构 SHIELDING STRUCTURE	包装米数 METERS/PACKAGING
16AWG (ID:2.2mm)	2C / 6.5mm	26/0.254TS	AL+112/0.10TS	100M
	3C / 6.8mm		AL+112/0.10TS	100M
	4C / 7.3mm		AL+128/0.10TS	100M
	5C / 7.9mm		AL+128/0.10TS	100M
	6C / 8.5mm		AL+128/0.12TS	100M
	7C / 8.7mm		AL+128/0.12TS	100M
	8C / 9.6mm		AL+144/0.12TS	100M
	9C / 10.4mm		AL+144/0.12TS	100M
	10C / 11.0mm		AL+144/0.12TS	100M
18AWG (ID:1.8mm)	2C / 5.8mm	34/0.178TS	AL+96/0.10TS	200M
	3C / 6.1mm		AL+96/0.10TS	200M
	4C / 6.6mm		AL+112/0.10TS	200M
	5C / 7.1mm		AL+112/0.10TS	100M
	6C / 7.6mm		AL+128/0.10TS	100M
	7C / 8.0mm		AL+128/0.10TS	100M
	8C / 8.5mm		AL+128/0.12TS	100M
	9C / 9.3mm		AL+128/0.12TS	100M
	10C / 9.8mm		AL+128/0.12TS	100M
20AWG (ID:1.5mm)	2C / 5.0mm	21/0.178TS	AL+80/0.10TS	200M
	3C / 5.3mm		AL+80/0.10TS	200M
	4C / 5.7mm		AL+96/0.10TS	200M
	5C / 6.1mm		AL+96/0.10TS	200M
	6C / 6.7mm		AL+112/0.10TS	200M
	7C / 6.9mm		AL+112/0.10TS	200M
	8C / 7.4mm		AL+112/0.10TS	100M
	9C / 8.0mm		AL+128/0.10TS	100M
	10C / 8.4mm		AL+128/0.10TS	100M

2464屏蔽系列聚氯乙烯绝缘电线

2464 SHIELDED SERIES PVC INSULATED WIRE

产品规格 PRODUCT SPECIFICATION	外径/OD OUTSIDE DIAMETER	导体结构 CONDUCTOR STRUCTURE	屏蔽结构 SHIELDING STRUCTURE	包装米数 METERS/PACKAGING
22AWG (ID:1.3mm)	2C / 4.5mm	17/0.16TS	AL+64/0.10TS	200M
	3C / 4.9mm		AL+64/0.10TS	200M
	4C / 5.3mm		AL+80/0.10TS	200M
	5C / 5.6mm		AL+80/0.10TS	200M
	6C / 6.1mm		AL+80/0.10TS	200M
	7C / 6.3mm		AL+96/0.10TS	200M
	8C / 6.7mm		AL+96/0.10TS	200M
	9C / 7.2mm		AL+112/0.10TS	100M
	10C / 7.6mm		AL+112/0.10TS	100M
24AWG (ID:1.2mm)	2C / 4.0mm	11/0.14TS	AL+48/0.10TS	200M
	3C / 4.4mm		AL+48/0.10TS	200M
	4C / 4.7mm		AL+64/0.10TS	200M
	5C / 5.1mm		AL+64/0.10TS	200M
	6C / 5.5mm		AL+80/0.10TS	200M
	7C / 5.7mm		AL+80/0.10TS	200M
	8C / 6.0mm		AL+96/0.10TS	200M
	9C / 6.5mm		AL+96/0.10TS	100M
	10C / 6.8mm		AL+96/0.10TS	100M
26AWG (ID:1.0mm)	2C / 3.5mm	7/0.16TS	AL+48/0.10TS	200M
	3C / 4.0mm		AL+48/0.10TS	200M
	4C / 4.1mm		AL+48/0.10TS	200M
	5C / 4.5mm		AL+64/0.10TS	200M
	6C / 5.0mm		AL+64/0.10TS	200M
	7C / 5.3mm		AL+64/0.10TS	200M
	8C / 5.5mm		AL+64/0.10TS	200M
	9C / 5.9mm		AL+80/0.10TS	200M
	10C / 6.2mm		AL+80/0.10TS	200M

2464屏蔽系列聚氯乙烯绝缘电线

2464 SHIELDED SERIES PVC INSULATED WIRE

[illegible]