


Dualflex RB 610 P

Telfon / PUR / 숫자 또는 색상코어 / 할로겐프리 / UL 토션 로봇케이블



RB 610 P



기술 데이터 Technical Data	
⚡ 사용전압 (Nominal voltage)	0.14mm ² ~ 0.34mm ² : Max. 250V 0.5mm ² ~ 1.5mm ² : (Uo/U) 300 / 500V 2.5mm ² ~ : (Uo/U) 450 / 750V
⚡ 시험전압 (Test voltage)	(Max. 250V) 2000V (300 / 500V) 2500V (450 / 750V) 4000V
⌒ 곡률반경 (Min. Bending Radius)	7.5 × d
🌡️ 사용온도 (Temperature range)	fixed laying -50°C ~ +105°C flexible application -40°C ~ +105°C
🔥 난연성 (Fire performance)	IEC 60332-1
🌀 비틀림 (Torsion)	Max. ±360° / m

케이블 구조 Cable Structure	
🔗 도체 (Conductor)	For extra-fine wire conductors DIN EN 60228, VDE 0295 (class 6)
🛡️ 절연 (Insulation)	Teflon
🔍 코어식별 (Core identification)	Black cores with consecutive numbers or color cores
📎 테이핑 (Binding)	e-PTFE tape
🧵 시스재질 (Jacket material)	PUR
🎨 시스색상 (Jacket color)	Black (RAL 9005)

제품 특징 Product Features
▶ Torsion Angle ±360° / m

유사 제품 Similar Products
▶ DUALFLEX RB 605P

품목코드 (Item Code)	선심수 × 도체단면적 (Cores × Cross section (No. × mm ²))	케이블 외경 (Outer diameter (mm))	도체중량 (Copper weight (kg/km))	케이블 중량 (Cable weight (kg/km))
1504-0702	7 × 0.25	6.2	16.1	46.8
1504-0203	2 × 0.34	5.2	6.3	28.5
1504-0407	4 × 0.75	6.6	27.6	63.1
1504-1407	7 × 2 × 0.75	11.1	96.6	178.4
1504-0210	2 × 1.0	6.5	18.4	49.6
1504-0310	3 × 1.0	6.7	27.6	62.9
1504-0410	4 × 1.0	7.2	36.8	77.3
1504-0710	7 × 1.0	9.1	64.4	122.8
1504-1210	12 × 1.0	10.5	110.4	183.0
1504-1261	6 × 2 × 1.0	13.0	110.4	197.1
1504-1810	18 × 1.0	12.8	165.6	274.0
1504-1861	6 × 3 × 1.0	18.0	165.6	278.2

품목코드 (Item Code)	선심수 × 도체단면적 (Cores × Cross section (No. × mm ²))	케이블 외경 (Outer diameter (mm))	도체중량 (Copper weight (kg/km))	케이블 중량 (Cable weight (kg/km))
1504-1862	16 × 1.0 + (2 × 1.0)	14.7	165.6	308.3
1504-2510	25 × 1.0	15.1	230.0	378.7
1504-2561	7 × 3 × 1.0 + 4 × 1.0	23.0	230.0	368.5
1504-2562	23 × 1.0 + (2 × 1.0)	15.9	251.5	385.4
1504-3410	34 × 1.0	16.8	312.8	496.4
1504-4110	41 × 1.0	17.9	377.2	587.5
1504-1815	18 × 1.5	15.0	248.4	393.9
1504-0325	3 × 2.5	8.8	69.0	120.7
1504-0425	4 × 2.5	9.7	92.0	154.2
1504-0361	3 × 16	21.1	442.4	648.9
1504-0362	3 × 25	25.9	691.2	1060.2
1504-0363	3 × 35	28.5	967.7	1403.1

OPTIONAL

 요청시 UL인증완료된 케이블 생산 가능합니다.