

COMPANY PROFILE

公司简介

深圳市宏观盛科技有限公司

SHENZHEN HONGGUANSHENG SCIENCE AND TECHNOLOGY LTD.

深圳市宏观盛科技有限公司成立于2010年，公司坐落于深圳龙岗，注册资金500万元，是国内一家集研发、生产、加工销售为一体的综合型电线电缆生产企业。

产品广泛用于电子电器、照明灯具、电子设备、机械电气、电热制品及汽车工业。

SHENZHEN HONGGUANSHENG SCIENCE AND TECHNOLOGY LTD. WAS FOUNDED IN 2010 AND LOCATED IN SHENZHEN, WITH A REGISTERED CAPITAL OF 5 MILLION YUAN. WE ARE A COMPREHENSIVE STRENGTH COMPANY THAT INTEGRATES TECHNOLOGICAL R&D, MANUFACTURING, PROCESSING AND SALES. OUR PRODUCTS ARE WIDELY USED IN ELECTRONIC APPLIANCES, LIGHTING LAMPS, ELECTRONIC EQUIPMENT, MECHANICAL AND ELECTRICAL, ELECTRIC HEATING PRODUCTS AND AUTOMOTIVE INDUSTRY.

公司主营产品为:1007、1015、1571、1061、1672、2651、2725、20276、2835、1617、1095、1569、2517、2468、2464、1533、1185、2547等PVC电子线，RVB红黑线、RVVB电源线、RV、BVR、BVV电线、RVV电缆线、RVVP屏蔽线、耐油耐温电线电缆、对绞电缆、硅胶线 铁氟龙 编织高温线云母高温线等系列产品。

1007,1015,1571,1061,1672,2651,2725,20276,2835,1617,1569,2517,2468,2464,1533,1185,2547ETC. PVC ELECTRONIC WIRE, RVB RED AND BLACK WIRE, RVVB POWER CORD, RV,BVR,BVV WIRE, RVV CABLE, RVVP SHIELDED WIRE, OIL AND TEMPERATURE RESISTANT WIRE AND CABLE, PAIR OF TWISTED CABLE, SILICONE WIRE, TEFLON, WOVEN HIGH TEMPERATURE WIRE MICA HIGH TEMPERATURE WIRE AND OTHER PRODUCTS.

创新科技 专业专注

INNOVATION, PROFESSIONAL & FOCUS

产品严格按照ISO9001质量管理体系标准生产，每道环节有专门的质检人员把关，拥有多台质检设备。产品选用NP级原料，不含邻苯二甲酸，环保无毒，环保级别更是在ROHS之上，我们拥有多项产品专利，汇聚众多高素质管理人员和专业技术人员，致力于为消费者打造安全放心的品质线缆。

PRODUCTS IN STRICT ACCORDANCE WITH THE ISO9001 QUALITY MANAGEMENT SYSTEM STANDARD PRODUCTION. EACH LINK HAS A SPECIAL QUALITY INSPECTION PERSONNEL CHECK, WITH A NUMBER OF QUALITY INSPECTION EQUIPMENT. NP GRADE RAW MATERIALS ARE SELECTED FOR THE PRODUCT, PHTHALATE FREE, ENVIRONMENTAL AND NON-TOXIC, ENVIRONMENTAL PROTECTION LEVEL IS ABOVE ROHS. WE HAVE A NUMBER OF PRODUCT PATENTS, BRING TOGETHER A LARGE NUMBER OF HIGH-QUALITY MANAGEMENT TEAMS AND PROFESSIONAL TECHNICAL PERSONNEL, COMMITTED TO CREATING SAFE AND RELIABLE QUALITY CABLES FOR CONSUMERS.

公司资质 / CERTIFICATE

UL认证

CE认证

ISO9001



专利证书/PATENT



产品参数

PARAMETER

产品名称:	2547屏蔽线
Product Name	2547 Shielded wire
额定电压:	300V
Rated Voltage	
额定耐温:	80℃
Temperature resistance	
导体材质:	环保镀锡铜丝
Conduct Material	Tinned copper wires
绝缘材质:	PVC
Insulation Material	
产品认证:	UL
Product Certification	
环保标准:	RoHS、NP
Environmental Standards	



芯线颜色

COLOR

2C	3C	4C	5C	6C	7C	8C	9C	10C
红 白	红 白 黄	红 黑 黄 白	红 黑 黄 白 棕	红 黑 黄 白 绿 蓝	红 黑 黄 白 绿 蓝 棕	红 黑 黄 白 绿 蓝 棕 橙	红 黑 黄 白 绿 蓝 棕 橙 灰	红 黑 黄 白 绿 蓝 棕 橙 灰 紫
Red/Black	Red/Black/Yellow	Red/Black/Yellow White/Green	Red/Black/Yellow/White/Brown	Red/Black/Yellow/White/Green/Blue	Red/Black Yellow/White/ Green/Blue Brown	Red/Black Yellow/White/ Green/Blue Brown/Orange	Red/Black Yellow/White/ Green/Blue Brown/Orange Grey	Red/Black Yellow/White/ Green/Blue Brown/Orange Grey/Purple

产品特点

PRODUCT FEATURES

- ◆适用于数码相机、仪器仪表、充电器、音响、医疗设备、玩具、家用电器及电路板等领域
- ◆长期允许工作温度应不超过70℃
- ◆具有柔软性、抗酸性、耐油性、防潮、防霉等特性

- ◆ APPLICABLE TO DIGITAL CAMERAS, INSTRUMENTS, CHARGERS, AUDIO, MEDICAL EQUIPMENT, TOYS, HOUSEHOLD APPLIANCES AND CIRCUIT BOARDS AND OTHER FIELDS
- ◆ THE LONG-TERM ALLOWABLE WORKING TEMPERATURE SHALL NOT EXCEED 70 ℃.
- ◆ WITH SOFTNESS, ACID RESISTANCE, OIL RESISTANCE, MOISTURE-PROOF, MILDEW-PROOF AND OTHER CHARACTERISTICS

2547屏蔽系列聚氯乙烯绝缘电线

2547 SHIELDED SERIES PVC INSULATED WIRE

产品规格 PRODUCT SPECIFICATION	外径/OD OUTSIDE DIAMETER	导体结构 CONDUCTOR STRUCTURE	屏蔽结构 SHIELDING STRUCTURE	包装米数 METERS/PACKAGING
14AWG (ID:2.5mm)	2C / 6.5mm	80/0.16TS	80/0.12TS	100M
	3C / 7.0mm		85/0.12TS	100M
	4C / 7.6mm		90/0.12TS	100M
	5C / 8.0mm		95/0.12TS	100M
	6C / 9.0mm		100/0.12TS	100M
	7C / 9.2mm		105/0.12TS	100M
	8C / 10.0mm		110/0.12TS	100M
	9C / 11.0mm		115/0.12TS	100M
	10C / 11.7mm		112/0.12TS	100M
16AWG (ID:2.1mm)	2C / 5.6mm	50/0.16TS	105/0.10TS	200M
	3C / 6.0mm		110/0.10TS	200M
	4C / 6.5mm		115/0.10TS	200M
	5C / 7.1mm		85/0.12TS	100M
	6C / 7.7mm		90/0.12TS	100M
	7C / 7.9mm		95/0.12TS	100M
	8C / 8.5mm		100/0.12TS	100M
	9C / 9.4mm		105/0.12TS	100M
	10C / 10.0mm		110/0.12TS	100M
18AWG (ID:1.5mm)	2C / 5.0mm	21/0.178TS	80/0.12TS	200M
	3C / 5.3mm		80/0.12TS	200M
	4C / 5.7mm		80/0.12TS	200M
	5C / 6.1mm		80/0.12TS	200M
	6C / 6.7mm		80/0.12TS	200M
	7C / 6.9mm		80/0.12TS	200M
	8C / 7.4mm		80/0.12TS	100M
	9C / 8.0mm		80/0.12TS	100M
	10C / 8.4mm		80/0.12TS	100M

2547屏蔽系列聚氯乙烯绝缘电线

2547 SHIELDED SERIES PVC INSULATED WIRE

产品规格 PRODUCT SPECIFICATION	外径/OD OUTSIDE DIAMETER	导体结构 CONDUCTOR STRUCTURE	屏蔽结构 SHIELDING STRUCTURE	包装米数 METERS/PACKAGING
20AWG (ID:1.4mm)	2C / 4.2mm	21/0.16TS	75/0.10TS	300M
	3C / 4.5mm		90/0.10TS	300M
	4C / 4.8mm		95/0.10TS	300M
	5C / 5.3mm		105/0.10TS	200M
	6C / 5.6mm		110/0.10TS	200M
	7C / 5.9mm		115/0.10TS	200M
	8C / 6.3mm		85/0.12TS	200M
	9C / 6.8mm		90/0.12TS	100M
	10C / 7.3mm		95/0.12TS	100M
22AWG (ID:1.2mm)	2C / 3.7mm	17/0.14TS	60/0.10TS	300M
	3C / 3.9mm		65/0.10TS	300M
	4C / 4.2mm		70/0.10TS	300M
	5C / 4.5mm		80/0.10TS	300M
	6C / 4.8mm		85/0.10TS	300M
	7C / 5.1mm		90/0.10TS	300M
	8C / 5.4mm		95/0.10TS	300M
	9C / 5.9mm		110/0.10TS	200M
	10C / 6.4mm		115/0.10TS	200M
24AWG (ID:1.1mm)	2C / 3.2mm	11/0.14TS	55/0.10TS	300M
	3C / 3.4mm		60/0.10TS	300M
	4C / 3.6mm		65/0.10TS	300M
	5C / 3.9mm		75/0.10TS	300M
	6C / 4.3mm		80/0.10TS	300M
	7C / 4.6mm		85/0.10TS	300M
	8C / 4.9mm		90/0.10TS	300M
	9C / 5.4mm		95/0.10TS	200M
	10C / 5.8mm		110/0.10TS	200M

2547屏蔽系列聚氯乙烯绝缘电线

2547 SHIELDED SERIES PVC INSULATED WIRE

[illegible]